

AMERICAN

CINEMATOGRAPHER

The Motion Picture CAMERA Magazine

December
1935

Published in Hollywood

American Society
Cinematographers



this issue

25c

Technical Progress in 1935
New 20th Century Camera
Controlling Reproductions
Destroying Pompeii
... and other features



★ **DU PONT NEGATIVE**



REG. U.S. PAT. OFF.

DU PONT FILM MANUFACTURING CORPORATION

35 WEST 45TH STREET
NEW YORK CITY

PLANT . . . PARLIN, N. J.

SMITH & ALLER LTD.

6656 . . SANTA MONICA BLVD.

HOLLYWOOD, CAL.

Photographed
by
**GEORGE
FOLSEY**



Photographed
by
**RAY
JUNE**



Photographed
by
**THEODOR
SPARKUHL**



THE



TRADEMARK HAS NEVER BEEN PLACED ON AN INFERIOR PRODUCT

REG. U.S. PAT. OFF.

AMERICAN CINEMATOGRAPHER

A Technical and Educational publication
of motion picture photography.

Published monthly by the
AMERICAN SOCIETY
OF CINEMATOGRAPHERS, INC.
6331 Hollywood Boulevard
Hollywood, California

Telephone GRanite 2135

JOHN ARNOLD, President, A.S.C.
FRED JACKMAN, Treasurer, A.S.C.

Volume 16 DECEMBER 1935 Number 12

What to Read

TECHNICAL Progress in 1935.....	512
PROBLEMS of Controlling Correct Photographic Reproductions by Dr. Herbert Meyer, A.S.C.....	514
AN ETCHER of Character by Harry Burdick.....	515
INNOVATIONS Mark New 20th Century Camera by Wm. Stull, A.S.C.....	516
COMPLETE Laboratory in One Unit by George Schneiderman, A.S.C.....	518
DESTROYING Pompeii in Miniature by Edwin C. Linden, A.S.C.....	519

Next Month

- Dr. Herber Meyer will give us another comprehensive and instructive article on the laboratory side of the motion picture business. We will also have a fine contribution from the head of one of the camera departments of a Hollywood studio on Standardizing Camera Equipment.
- Naturally there will be a pen picture of one on the leading Directors of Cinematography and other contributions by members of the American Society of Cinematographers.



The Staff

EDITOR

Charles J. VerHalen

TECHNICAL EDITOR

Emery Huse, A. S. C.

ASSOCIATES

Karl Hale

Walter Blanchard

CIRCULATION MANAGER

M. E. Fisher

ADVISORY EDITORIAL BOARD

Victor Milner, A. S. C.
James Van Trees, A. S. C.
Fred Jackman, A. S. C.
Farciot Edouart, A. S. C.
Fred Gage, A. S. C.
Dr. J. S. Watson, Jr., A. S. C.
Dr. L. M. Dieterich, A. S. C.
Dr. L. A. Jones, A. S. C.
Dr. C. E. K. Mees, A. S. C.
Dr. W. B. Rayton, A. S. C.
Dr. Herbert Meyer, A. S. C.
Dr. V. B. Sease, A. S. C.

FOREIGN REPRESENTATIVES

Georges Benoit, 100, Allee Franklin,
Pavillons-sous-Bois, France. Seine. Tele-
phone LeRaincy 13-19.

NEW YORK REPRESENTATIVE

S. R. Cowan, 19 East 47th St., New York
City. Phone Plaza 3-0483.

Neither the American Cinematographer nor the American Society of Cinematographers is responsible for statements made by authors. This magazine will not be responsible for unsolicited manuscripts.



ESTABLISHED 1918. Advertising Rates on application.
Subscription: U.S. \$2.50 a year; Canada \$3.50 a year;
Foreign \$3.50 a year. Single copies 25c. Foreign
single copies 35c. COPYRIGHT 1935 by American
Society of Cinematographers, Inc.

AMERICAN SOCIETY OF CINEMATOGRAPHERS

OFFICERS

JOHN ARNOLD	President
VICTOR MILNER	First Vice-President
JAMES VAN TREES	Second Vice-President
CHARLES LANG	Third Vice-President
FRED JACKMAN	Treasurer
FRANK B. GOOD	Secretary

BOARD OF GOVERNORS

John Arnold	Frank Good
Bert Glennon	Fred Jackman
Dan Clark	Ray June
Elmer Dyer	Charles B. Lang, Jr.
Arthur Edson	Victor Milner
George Folsey	Joseph Walker
Alfred Gilks	James Van Trees
	Vernon L. Walker

Frederick L. Kley, Executive Business Manager

PAST PRESIDENTS

Philip E. Rosen	Hal Mohr
Gaetano Gaudio	Homer Scott
James Van Trees	John F. Seitz
John W. Boyle	Daniel B. Clark
	Fred W. Jackman

HONORARY MEMBERS

Mr. Albert S. Howell
Mr. Edward O. Blackburn
Mr. George A. Mitchell

PUBLIC RELATIONS COMMITTEE

John Arnold
Joseph Ruttenberg, New York City
Charles Bell, St. Paul, Minn.
Charles J. Davis, Washington, D. C.
Georges Benoit, Paris, France
John W. Boyle, London, England
Ariel Vargas, Tokyo, Japan
Edwin L. Dyer, Detroit, Mich.
Charles W. Herbert, New York City
Lloyd Knechtel, London, England
John Dored, Paris, France
Paul Perry, Manila, P. I.
Max B. DuPont, Papeete, Tahiti
Philip M. Chancellor

MEMBERSHIP COMMITTEE

George Folsey	Dan Clark
Alfred Gilks	Robt. Pittack
Bert Longworth	Fred Terzo

ENTERTAINMENT COMMITTEE

Elmer Dyer	Frank B. Good
Charles B. Lang, Jr.	Vernon Walker
	Arthur Edson

WELFARE COMMITTEE

Ray June	James Van Trees
	Fred W. Jackman

GENERAL COUNSEL

Arthur C. Webb

RESEARCH COMMITTEE

Victor Milner, George A. Mitchell, Dr. Herbert Meyer, John Arnold, Farciot Edouart, Emery Huse, Dr. L. M. Dietrich

Directors of Photography

Abel, David
Andersen, Milford A.
Andriot, Lucien
Arnold, John
Ash, Jerome H.
August, Joseph

Ballard, Lucien
Barlatier, Andre
Barnes, George S.
†Bell, Chas. E.
†Benoit, Georges
†Boyle, Chas. P.
†Boyle, John W.
Brodine, Norbert F.
*Browne, Fayte M.

Chancellor, Philip
Clark, Dan
Clarke, Charles G.
*Contner, J. Burgi
Corby, Francis
Cronjager, Edward
†Crosby, Floyd D.

Daniels, William H.
†Davis, Charles J.
Dean, Faxon
de Grasse, Robert
Depew, Ernest S.
DeVinna, Clyde
†Dored, John
Draper, Lauron A.
*Dubray, Joseph A.
DuPar, E. B.
Dyer, Edwin L.
Dyer, Elmer G.

Edson, Arthur

Fernstrom, Ray
Fischbeck, Harry
Folsey, George J., Jr.
Forbes, Harry W.
†Foster, Ray
Freulich, Henry
*Freund, Karl
Fryer, Richard

Galezio, Len
Gaudio, Gaetano
Gerstad, Merritt B.
Gilks, Alfred
Glennon, Bert
Good, Frank B.

Haller, Ernest
Halperin, Sol
†Harten, Charles
*Haythorne, Reed N.
†Herbert, Charles W.
Herrmann, John L.
Hickox, Sid
Hickson, John T.
Howe, James Wong
Hunt, Roy

Ivano, Paul

Jackson, Harry
June, Ray

Kershner, Glenn
Kline, Ben
†Knechtel, Lloyd
Kohler, Henry N.
Krasner, Milton
Kull, Adolph E.

Landers, Sam
Lang, Charles B., Jr.
†Levitt, Sam
Linden, Edwin G.
Lloyd, Art
Lundin, Walter
Lyons, Chet

MEMBERS

MacDonald, Joe
Mackenzie, Jack
†MacWilliams, Glenn
Malkames, Don
Marley, J. Peverell
Marsh, Oliver
Marshall, Chas. A.
Marshall, William C.
Martinelli, Arthur
Marzorati, Harold J.
Mate, Rudolph
**Mayer, Fred
McCord, Ted
McGill, Barney
Meehan, Geo. B., Jr.
Mellor, William C.
Mescall, John J.
Miller, Arthur
Miller, Virgil E.
Milner, Victor
Mohr, Hal
Morgan, Ira H.
Musuraca, Nick

Neuman, Harry C.

O'Connell, L. William
Overbaugh, Roy F.

Palmer, Ernest
Peach, Kenneth
Perry, Harry
†Perry, Paul P.
Peterson, Gus C.
Planck, Robert H.
Polito, Sol

**Ragin, David
Rees, William A.
Reynolds, Ben F.
Robinson, George
Rose, Jackson J.
Rosher, Charles
Rossos, Harold
Ruttenberg, Joseph

Schneiderman, George
Schoenbaum, Charles
Seitz, John F.
Shackelford, James B.
Shamroy, Leon
Sharp, Henry
*Shearer, Douglas
Sickner, Wm. A.
Siegler, Allen
†Silver, John
Smith, Jack
Smith, Leonard
Snyder, Edward J.
Sparkuhl, Theodor
†Steiner, William, Jr.
Stengler, Mack
Stout, Archie J.
Streng, Walter
Struss, Karl
Stumar, John

Taylor, J. O.
Tetzlaff, Ted
Thompson, Allen Q.
Thompson, William C.
**Tobey, Robert
Todd, Arthur
Toland, Gregg
Tover, Leo
Towers, Richard
**Trego, Chas. T.
Tutwiler, Tom

Valentine, Joseph A.
*Van Buren, Ned
†Vander Veer, Willard
Van Trees, James
†Vargas, Ariel
von Sternberg, Josef

Wagner, Sidney C.
Walker, Joseph
Warren, Dwight
Warrenton, Gilbert
Wenstrom, Harold
Wetzel, Al
Wheeler, William
White, Lester
Wyckoff, Alvin

†Zucker, Frank C.

Special Process

Binger, Ray

Culiy, Russell A.

Dietz, Wm. H.

Eagler, Paul
*Edouart, Farciot

Fabian, Maxmillian
Fulton, John P.

Griggs, Loyal

Hammeraas, Edwin
Haskin, Byron

*Jackman, Fred
Jackman, Fred, Jr.
*Jennings, Gordon
Jennings, J. D.

Kelley, W. Wallace
Koenekamp, H. F.

†Lipp, Leo
Lipstein, Harold
Lynch, Warren

Pollock, Gordon

Ries, Irving C.
Roberts, Irmin

Smith, Arthur

Van Enger, Willard

*Walker, Vernon L.
Williams, William N.
Wrigley, Dewey
Wimpy, Rex

†Zech, Harry

Operative Cinematographers

Ahern, Lloyd
Albert, C. L.
Anderson, Don
Anderson, Wesley
Arling, Arthur E.

Badaracco, Jacob
Bader, Walter
Bell, Jack C.
Bennett, Guy M.
Bennett, Monroe
Bentley, Fred
Biroc, Joe
Blackstone, Cliff
Booth, Frank H.
Boyce, Rube
Bradley, Wilbur H.
Brangan, Thomas
Burks, Robert

Castle, Walter H.
Chewning, Wallace
Clark, Roy
Clemens, Geo. T.
Cline, Wilfrid M.
Cohen, Edward J.
Collings, Russell D.
Cortez, Stanley

Davis, Harry
Davis, Leland E.
Diamond, Jas. R.
Drought, James B.
Dunn, Linwood G.

Eslick, LeRoy
Estabrook, Edw. T.

Fapp, Daniel L.
Feindel, Jockey
Fetters, C. Curtis
Finger, Frank
Finger, John
Fitzgerald, Edward

MEMBERS

Garnett, Paul
Gertsman, Maury
Gibbons, Jeff T.
Glassberg, Irving
Gordon, James
Gray, King D.
Green, Kenneth
Greene, Al M.
Guffey, Burnett
Guthrie, Carl

Hallenberger, Harry
Harlan, Russell
Harper, James B.
Harris, Emil
Heckler, Wm. G.
Henderson, Edward
Hoag, Robert
Huggins, L. Owens

Irving, Allen E.

Jennings, Louis E.
Jones, Allyn C.
Joyce, Michael T.

Kelley, George F.
†Kelly, Wm. J.
Kesson, Frank
Knott, James

Landon, Theodore
Lane, Al L.
Lanning, Reggie
LaShelle, Joseph
Laszlo, Ernest
Lawton, Charles C.
Lerpae, Paul K.
Lindon, Lionel A.
Love, Cecil

Marlatt, Mark W.
Marra, Jack A.
McCormick, John T.
Meade, Kyme
Merland, Harry
Metty, R. L.
Mols, Pierre M.
Myers, Albert

Newhard, Guy J.
Newhard, Robert S.
Nogle, Geo. G.
Novak, Joe

Palmer, Robert
Pierce, Otto
Pittack, Robert
Pyle, Edwin L.

Ramsey, H. Clark
Ramsey, Ray L.
Rand, William
Redman, Frank
Ries, Ray
Roberts, Albert G.
Roberts, Josiah
Robinson, Walter C.
Roe, Guy
Rosenberg, Irving

Salerno, Charles, Jr.
Scheurich, Victor
Schmitz, John J.
Schurr, William F.
Schoedsack, G. F.
Shipham, Bert
Smith, Ernest F.
Smith, Harold I.
Smith, William Cooper
Snyder, Wm.
Stine, Clifford R.
Sullivan, Wm. F.
Surtees, Robt. L.

Tappenbeck, Hatto
Thompson, Stuart
Titus, Frank

Ulm, William R.
Unholz, George
Vaughan, Roy V.
Vogel, Paul Charles
Vogel, Willard I.

Webb, Harry
Wester, Carl
White, Ben
Wild, Harry
Wilky, L. Guy
Williams, Al E.
Williamson, James

Young, Jack R.

Assistant Cinematographers

Abbott, L. B.
Abramson, Melvin
Adams, Eddie
Adams, Ralph G.
Andersen, Jack
Anderson, Eddie
August, Joseph S.

Babbitt, Royal F.
Baldwin, Herold
Barber, E. C.
Barth, Willard
Beckner, Neal
Bergholz, Emmett
Bessette, Raoul
Boggs, Haskell
Bohny, Chas. R.
Bourn, George
Bradford, Bill
Bridenbecker, Milton
Brigham, Donald H.
Bronner, Robert
Buchholz, Frank H.
Burgess, Frank
Burke, Charles

Cairns, Lawrence
Caldwell, John C.
Carney, Harold F.
Carrer, Ellis W.
Citron, Joseph A.
Clothier, William H.
Cohan, Ben
Cohen, Sam
Collins, Edward C.
Crane, Chas. M.
Crawford, Lee
Crockett, Ernest J.
Cronjager, Henry, Jr.
Crouse, John
Cruze, Warner
Curtiss, Judd

Daly, James
Dalzell, Arch R.
Davenport, Gene L.
Davis, Mark
Davis, Robt. D., Jr.
Daval, Richard S.
Dawe, Harry
Dawson, Fred
DeAngelis, Louis
†De Castellaine, Paul
Deverman, Dale
Diskant, George
Dodds, Wm.
Doran, A. Richard
Dorris, Joseph
Dowling, Thomas L.
Dugas, Frank
Dye, Geo., Jr.

Eagan, J. P.
Eason, Bert
Eckert, John
Elliott, August J.
Epstein, Jack J.
†Etra, Jack
Evans, Frank D.

Farley, Joseph L.
Finnerman, Perry
Fischer, Herbert J.
Foxall, William
Fredricks, Ellsworth

Garvin, Edward
Gaudio, Frank, Jr.
Geissler, Charles R.
Gerstle, Arthur
Goss, James M., Jr.
Gough, Robt. J.
Graham, Harold W.
Grand, Marcel
Grant, James Arthur
Green, Don
Greer, John

Hackett, James C.
Haddow, Ledger
Hayes, Towne D.
Higgins, James Colman
Higgs, Stuart P.
Hoffman, Roswell
Holahan, Richard J.
†Holcombe, Walter B.
Hoover, Russell C.
Horslev, D. S.
Hunter, Kenneth
Hyland, Edward

Ivey, Jesse

Jolley, Wm. A., Jr.
Jones, Edward C.

Kaifer, Fred E.
Kauffman, R. King, Jr.
Kearns, Edward
Keller, Alfred S.
Kenny, Jack
King, James V.
Klein, Irving
Kluznik, Mart
Koffman, Jack
Kunkel, Lou E.

Lackey, Walter K.
Lane, Art
Laraby, Nelson
Larson, Vernon
Lathrop, Philip
Leahy, Chas. P.
Lebovitz, Alfred
Lerpee, Carl
Lewis, C. L.
Liggett, Eugene
Lockwood, Paul
Lykins, Vollie Joe

Mack, Robt. H.
MacBurnie, John
MacDonnell, Stanley
Marble, Harry
Margulies, Bill
Martin, John
Martinelli, Enzo
Mautino, Bud
McDonald, Frank
McEdward, Nelson C.
McIntyre, Andy
Meade, Kenneth
Mehl, John
Mohn, Paul
Molina, Luis
Moore, Bernard
Moreno, Robert C.
Morris, Thomas C.

Nickolaus, John M., Jr.
Noble, Roy Wm.
Norton, Kay

Orsatti, Alfred

Parkins, Harry
Perreault, Oliver D.

Rankin, Walter
Reinhold, Wm. G.
Rhea, Robert
Riley, William
Rugs, Maynard B.
Russell, John L., Jr.

Sanford, S. A.
Sargent, Don
Scheving, Albert
Schuch, William
Seawright, Byron
Shearman, Roger C.
Shirpsen, C.

Shorr, Lester
Slifer, Clarence
Smalley, Alfred E.
Smith, Dave
Smith, H. C.
Soderberg, Edward F.
Southcott, Fleet
Straumer, E. Charles
Strong, William M.

Terzo, Fred
Thomas, Jack
Tolmie, Rod
Tripp, Roy

Van Trees, James, Jr.
Van Wormer, John Pierce

Walsh, Mike
Ward, Lloyd
Weddell, Paul K.
Weiler, Carl
Weiler, John
Weisbarth, Ted
Weissman, Leonard
Wellman, Harold
Wendall, Jack E.
White, Edward L.
Whitley, William
Willis, Bert
Worth, Lothrop

Still Photographers

Alexander, Kenneth
Allan, Ted
Alsop, George
Anderson, Bert
Aper, Virgil
Autrey, Max
Bachrach, Ernie
Bjerring, Frank
Blanc, Harry
Breaud, Joseph F.
Bredell, Elwood
Brown, Milton
Bull, Clarence S.
Bullock, Chas. E.
Bullock, Malcolm

Clark, Sherman L.
Coburn, Robert
Cooper, John
Cronenweth, W. E.
Crosby, Warner N.
Crowley, Earl

Elliott, Mack
Ellis, John
English, Donald A.
Estep, Junius D.
Evans, Thomas
Evansmith, Henry

Farrell, David H.
Freulich, Roman
Fryer, Elmer

Gillum, Don
Gillum, Tad A.
Gold, Milton
Graves, Clarence "Stax"
Graybill, Durward
Grimes, William H.

Head, Gordon G.
Hendrickson, Fred S.
Hester, Jerome E.
Hewitt, Clarence B.
Hommell, Geo. P.
Hopcraft, N. John

Johnson, Roy L.
Jones, Raymond H.
Julian, Mac

Kahle, Alexander
Keyes, Donald B.
Kling, Clifton
Kornmann, Gene

Lacy, Madison S.
Leiber, Herman
Lippman, Irving
Lobben, C. Kenneth
Longet, Gaston
Longworth, Bert
Lynch, Bert

MacDonald, Melvin A.
MacLean, Roy D.
Manatt, S. C.
Marigold, Mickey
Martin, Shirley Vance
Maupin, Clifton
McAlpin, Hal A.
McNulty, Stephen
Miehle, John J.
Milligan, Joseph C.
Morrison, Talmage H.

Nolan, Raymond G.

Osborne, Harry

Parrish, Fred A.
Paul, M. B.
Powolny, Frank

Richardson, G. E.
Richee, Eugene R.
Robbins, Leroy S.
Rowley, Les

Schafer, Adolph L.
Schoenbaum, Emmett A.
Sibbald, Merritt J.
Sigurdson, Oliver
Six, Bert
Stone, Ed

Tanner, Frank
Thomas, Wm. E.

Ugrin, Anthony

Van Pelt, Homer

Walling, Will, Jr.
Weilbourne, Chas. Scott
Wyckoff, Harold M.

Honorary Members

Mr. E. O. Blackburn,
Los Angeles, Calif.
†Mr. George Eastman,
Rochester, N. Y.
†Mr. Thomas A. Edison,
Orange, N. J.
Mr. Albert S. Howell,
Chicago, Ill.
Mr. George A. Mitchell,
Los Angeles, Calif.

Associate Members

Mr. Louis A. Bonn
Mr. George Cave
Dr. L. M. Dieterich
Mr. Fred Gage
Mr. Emery Huse
Dr. Lloyd A. Jones
Dr. C. E. K. Mees
Dr. Herbert Meyer
Mr. Hollis Moyse
Dr. W. B. Rayton
Dr. V. B. Sease
Dr. J. S. Watson, Jr.

Inactive Members

Dunning, Dodge
DuPont, Max B.
Fildew, William
Glouner, Martin G.
Graham, Stanley
Jackman, Dr. Floyd
Lockwood, J. R.
†Paul, Edward F.
Roos, Len H.
Slone, James
Stull, William

ANNUAL TOPIC INDEX.

Volume XVI, 1935

TOPIC INDEX—PROFESSIONAL

- Academy Award: 141.
Air, color in the: 380.
Air photography, "Lighting" problem in the: 243.
Air, streamlined cameras for: 430.
- Blimp, lightweight: 246.
Blimp, National: 148.
Byrd's Expedition: 241.
- Camera, explanation of technique: 8.
Camera, new Fried: 62.
Camera, new 20th Century: 516.
Cinematography, artistic honesty in: 94.
Color in the air: 380.
Color, help or hinder?: 100.
Color, "still" photography in natural: 422; 466.
Composition: 138.
- Detail, Haller stresses: 96.
Dolly head, adjustment for: 246.
- Editing: 138.
Editing sound device: 148.
Editorials: 189; 238.
Effects: 519.
- Glaciers in Alaska, shooting: 98.
- Improvements for efficiency: 239.
Influence, American Cinematographers: 53.
Interpreting personality and character: 97.
- Laboratory work: 514; 518.
Lamp, wide range spot: 282.
Lamp, Mercury Vapor: 93.
Light, creating moods with: 7.
Light, possibilities of Polarized: 330.
Lighting: 239.
Lighting, expressing tempo in: 54.
Lighting equipment, modern: 424.
Lighting problem in air photography: 243.
Lights, arc: 469.
"Luxurious," Struss' photography: 52.
- Makeup: 188; 286.
"Midsummer," photography is star of: 472.
Miniature: 519.
Movement, camera: 46.
- Negative Super X Panchromatic film: 186.
- Omniscient eye, camera's: 95.
- Pola-screens, practical angles in use of: 374.
Polarized light, possibilities of: 330.
Prints, release prints reflect cinematography: 379.
Processing glow lamp sensitometry: 192.
Progress of 1935, technical: 512.
- Recording "One Night of Love": 140.
Russia, training cinematographers in: 335.
- Sensitometry: 11.
Sensitometry, processing glow-lamp: 192.
Slide rule, photographic: item, 390.
Sound editing device: 148.
Sound recording developments: 284.
Sound-tracks, mechanographic recording for: 426.
South Pole, on location at the: 241.
Super X Panchromatic motion picture negative film: 186.
- Technicolor, explanation of the Trichrome: 8.
Tempo in lighting: 54.
Third Dimensional Motion Pictures, possibilities of: 377.
Tropics, cinematography in the: 144.
- Vitality, Lang's photography has: 51.
- ### TOPIC INDEX—AMATEUR
- Animation: item, 172; 400.
- Backgrounds, process: 124.
Books, profitable: 167.
Book reviews: Photographic Annual for 1935: 38; Practical Amateur Photography: 86; Projection Control: 170; The Leica Data Book; Getting Ahead in Photography: 413; New Leica Manual: 458.
- Cameras, I would like to own: 213; 214; 270; 540.
Camera, silent 16mm. professional: 214.
Camera, DeVry sound: item, 540.
Camera, Bell & Howell 8mm.: item, 270.
Camera, Reflex box: 540.
Cartoons: 76.
Cinetricks with mirrors: 442.
Color: 118; 208; 262; 312; 413; 448.
Color chart, where to purchase: item, 413.
Color film, Eastman 16mm.: 208.
Color film for miniature cameras: 118.
Color Indoors: 448.
Composition: 536.
Composition: 444; 536.
Continuity, use: 358.
Continuities: 75; 168; 212; 268; 304; 310; 311; 358; 403; 534.
- Developers, negative and positive title: 172.
Documentary picture of farm, filming an: 304.
- Eclipse of the moon: 489.
Editing: 122; 401.
8mm film in 16mm width, why: item, 32.
8mm film, speed of: item, 492.
8mm film reduced from 16mm: item, 172.
8mm, prize winner: 69.
Emulsion remover: item, 215.
Exposure, single: item, 30.
- Fades, making: 537.
Film, 16mm color: 208.
Film, matte tricks with 16mm. negative: 353.
Film, reversing 16mm: 28.
Film, special effects with reversal: 211.
Film viewer, making a: 34.
Filmchart, Weston: 540.
Filmvisor: item, 215.
Filters: 350; 532.
Filters, light: item, 404.
Filter, new Harrison: item, 77.
Filter, neutral density: item, 492.
Finder, framing shots in the: item, 32.
Flood light, dishpan: 488.
Frame counter, accurate: 124.
- Gadgets: 309; 488; 535; 538.
- Home movie, miniature shots for: 68.
Humidor can, home-made: 34.
Humidor, Cine: item, 540.
- Indoor Kodachrome: 448.
- Laboratory work, negative positive home: 353; 396.
Leader, Agfa: item, 77.
Leica camera, autobiography: 72.
Leica winder: item, 77.
Lenses, Wide Angles and Telephotos: 26.
Lenses: item 450.
Lenses, new: item, 494.
Lenses, projection and apparent distortion: 70.
Lens perspective: 258.
Lens, spectacle: 490.
Library, use your: 167.
Light filters: item, 404.
Light tester: item, 404.
Lighting, adapting professional: 29.
Lighting the longshot: 486.
Lights, new: item, 359.
Lights, spot, making: 338.
- Makeup: 120; 162; 210; 264.
Matte tricks with 16mm. negative: 353.
Meter, distance: item, 270; item, 314.
Meter, new exposure: item, 359.
Miniature camera: 173.
Miniature camera, hyper-sensitizing film: item, 32.
Miniature camera, color film for: 118.
- Miniature camera, negative density formula: item, 32.
Miniature camera, reversible film for: 447.
Miniature camera shots for home movies: 68.
Mirror tricks: 442.
Music with movies: 74.
- Printer, building a 16mm.: 266.
Printer, 16mm.: item, 270.
Printing 16mm. negative on 35mm. stock: item, 32.
Projection, tips on home: 117.
Projection, perfecting home: 168.
Projector, new Bell and Howell: item, 77.
Projector, new Bell and Howell sound: item, 314.
- Reel, new 16mm. film: item, 30.
Reflectors: 533.
Retina Kodak: item, 30.
Reversal film, special effects with: 211.
Reversal home development: 306.
Reversed motion, continuity for: 75.
- San Diego Fair, Amateur Movie Day: 263.
Scenes, show it with added: 445.
Scenics: 532.
Ship's photographer: 491.
Shutters: 399.
Shutter speed, slowest: item, 32.
16mm., art director in: 398.
16mm., silent professional camera: 214.
Slow-motion: item, 450.
Sound camera, DeVry: item, 450.
Sound cartoons, synchronizing: 76.
Sound splicer: 450.
Sound 16mm. films, from 35mm.: 114.
Sound-on-film and common sense: 123.
Sound, non sync setup for silent pictures: 25.
Sound on silent 16mm. film, putting: 308.
Sound projector, new Bell & Howell: item, 314.
Substandard, German apparatus: 446.
Splicer, sound: item, 450.
Splicing Kodachrome film: item, 413.
- Tank agitator: item, 540.
Titles, contrast in: item, 414.
Titler, building a Universal: 164.
Traditions, breaking cine: 402.
Travel pictures: 354.
Tricks: 34; 124; 260; 356; 442.
Tricks, these things called: 355.
Tripod head, making a: 356.
- Viewer, intermittent film: 273.
- Wipes, gadget for making: 309.
Wipe off, new: item, 215.
Wipe Off, tricks with: 261.
Wipe Off, building a home made: 535.
Wipe Off: Victor, 540.



*Actual blowup of a 35 MM. frame
taken on Agfa film by Bernard
R. Hubbard, S. J., famous Glacier
Priest.*

AUDIENCES appreciate fineness of grain. And a majority of the compliments about splendid photography concern pictures made on fine-grain negative. Agfa's new, improved SUPERPAN is the last word in fineness of grain . . . and possesses everything else that should distinguish an ideal supersensitive panchromatic film. Made by Agfa Ansco Corporation in Binghamton, N. Y.



C. KING CHARNEY, Distributor

HOLLYWOOD

6372 SANTA MONICA BOULEVARD
TEL. HOLLYWOOD 2918-2919

NEW YORK

245 WEST 55TH STREET
TEL. CIRCLE 7-4635

RECOVERY from the depression is clearly indicated by the number of technical advances chronicled during 1935. In addition to a multitude of detail improvements, the year brought forth a number of advances of a basic nature; and although there was no change as radical as the introduction of Panchromatic film and Mazda lighting, or the advent of sound, none the less, certain of the year's innovations foreshadow sweeping changes which may logically be expected in the relatively near future. 1935 has indeed been a productive year.

Methods

There has been a marked tendency toward longer production-schedules and more generous budgets, permitting—if not actually demanding—the exercise of greater care in the technical departments.

There was also a definite increase in the number of location-made "Class A" productions, and in the utilization of bona-fide exterior scenes rather than stage-built exteriors or process shots.

Although, for various reasons, the Technicolor 'boom' which, early in the year many expected to follow the release of "Becky Sharp," the first three-color Technicolor feature, did not materialize, the later months have seen a revival of interest in all-color films, with several in production, and at least a score projected for the coming season. Abroad—especially in England—enthusiasm for color is reported at a high point.

In several studios definite progress was made toward standardization of photographic equipment.

Influence of Foreign Elements

The influence of foreign elements was not as marked as it has at times been in the past. Production in England made notable advances, economically, artistically and technically, drawing heavily upon Hollywood for expert technicians of all kinds, especially Cinematographers, special-process technicians, and make-up artists.

The tremendous interest in natural-color cinematography shown by the British film industry is directly responsible for the creation of a British branch of the Technicolor Corporation, and indirectly is undoubtedly an accelerating factor in the revival of Hollywood's interest in color.

Raw Materials

Eastman introduced "Super-X" Panchromatic negative film. This product, which was originally intended for use in photographing "transparency" or projected-background process composites, has come into general use for production camerawork. It is rated as 40 per cent faster than the previous Super Sensitive emulsion, with slightly different color-sensitivity characteristics, and requires an average of 2 minutes longer development.

Agfa introduced a 35mm. reversal-type Panchromatic film, of excellent characteristics. This product was intended primarily for the making of background-projection "key plates." However, due to the general need for post-development control of the density and contrast of these keys, the film has not been commercially used to a great extent. It is, however, spreading into the miniature-camera field with considerable success.

Agfa also introduced "Finopan" negative film, a medium-speed, fine-grain Panchromatic emulsion which is meeting considerable success as a film for transparency-background keys.

The Agfa firm likewise introduced an Infra-red sen-

sitive film which has been excellently received, and "Portrait Superpan" cut-film for 'still' photography.

The introduction of "Kodachrome" and "Dufaycolor" color-films (the former available only in 16mm., the latter in 16mm., 35mm., and roll, pack and cut-film) was of considerable importance.

In the substandard cinefilm field, aside from the advent of Kodachrome, Bell & Howell's introduction of pre-split 8mm. "Filmopan" was the greatest innovation.

Pellex introduced what is claimed to be the fastest Panchromatic emulsion yet produced in "Super-Pellex," which is given a Weston-meter speed rating of 50 for daylight and 40 for tungsten light. In common with all Pellex-films, it is of the reversal type (16mm.) and coated with the "Triplex" anti-halation backing, a part of which is left after processing to reduce projection-flare.

Cameras

The Twentieth Century Silent Camera, developed by Grover Laube and others at the 20th Century-Fox Studio, was probably the outstanding camera development of the year.

In the substandard field, Bell & Howell's "Straight 8 Film," using pre-split 8mm. film, set up a new 8mm. standard.

The Fearless Camera Co., of Hollywood, produced an interesting custom-built professional type 16mm. sound on film camera.

Abroad, the Zeiss "Movikon" exhibits many excellent features, especially a built-in range-finder coupled to the lens after the fashion of a miniature-camera, and the Siemens and others introduced inbuilt photocell exposure-meters interconnected with the diaphragm controls.

Accessories

The most startling innovation in this category was the development of the Eastman "Pola-Screen," a device for controlling glare, reflections, etc., by polarizing light.

Improvements in blimping were noted at Warner Bros. and Metro-Goldwyn-Mayer studios, and various forms of synchronizing lens and finder for follow-focus shots came into general use.

Metro-Goldwyn-Mayer developed an intermediate-sized camera-crane adapted to location work and high-speed transport as well as to studio use.

The Fox-Fearless "Velocitor" became standard equipment in many studios here and abroad, replacing tripods and earlier types of small cranes.

Lenses

Bell & Howell introduced a new super-speed lens for professional use, the new Taylor, Taylor & Hobson "cooke" f:1.3 "Speed Panchro."

Lighting

With faster films in use, there was a marked tendency toward the use of fewer lighting-units, but more efficient ones, and simpler lightings. The Arc made notable gains

Technical

Progress in 1935

in monochrome cinematography, due to the introduction of more modern equipments.

Mole-Richardson introduced the "Junior Solarspot," a Fresnel-lensed 2,000-watt unit producing a remarkably even beam of high power, which is rapidly supplanting the 18" parabolic-mirror reflector sunspot. A similar 5000-watt unit known as the "Senior Solarspot," is being introduced as this goes to press.

The same firm developed a Fresnel-lensed Arc spot-light known as the "HI-Arc," which is rapidly superseding both the 80 Ampere rotary-carbon condenser spot-light and the 24" (reflecting) Sun Arc. Although developed primarily for color cinematography, this lamp has been extensively used in black-and-white productions.

The "Vitachrome," an interesting, double-reflecting portrait lamp (1,000-2,000-watts) was introduced by A. C. Jenking.

Two high-power professional Photoflood units were introduced for industrial and location use. They are the "Artreeves," made by the Hollywood Motion Picture Equipment Co., and the Mole-Richardson "Cinelite."

In the amateur field, Lights, Inc., and Bell & Howell made available a range of aplanatic (faceted) metal reflectors for use with Photoflood globes.

Process Cinematography

No basic developments were noted, though many detail improvements were made by individuals and studios. Several films, released or in production, include unusual special-effects problems. Among them may be mentioned "The Last Days of Pompeii," "The Invisible Ray," "Peter Ibbetson," "A Midsummer Night's Dream," "Transatlantic Tunnel" (British), and "The Shape of Things to Come" (Also British).

Natural-color Cinematography

Professionally, the major interest in color is centered on Technicolor's three-color process, the only 3-tone method commercially available; but a considerable amount of undercover development work is under way by both studios and color-firms. With both "La Cucaracha" and "Becky Sharp" showing sufficient financial success to warrant the added expense of color photography and laboratory work, several American firms—notably Pioneer, Walter Wanger Productions, and Selznick-International—have scheduled a large group of color features for early

production. The number will probably total nearly a score. Abroad, Technicolor is erecting a plant to handle negative development, daily and release printing in England, and Alexander Korda's London Film Productions is reported to be planning an entirely Technicolor programme as soon as facilities are available, with other producers likewise interested in using the process.

With major-studio interest centered in Technicolor, independent producers and makers of short-subjects are giving various two-color processes a new lease on life. Coincidentally come improvements in some of these systems which, had they occurred before the commercial advent of three-color cinematography, would have been of front-rank importance. Among these are the use of single-coated prints and dichroic dyes by Cinecolor and the Dunning Tri-Tone process, the introduction of the Harrison Multichrome System and the Gilmore system, both of which produce two color-separation negatives on a single film by use of optical units which divide the picture into two half-size images, rotated 90° and occupying one normal frame; printing is done optically, with the images restored to normal size and position, superimposed and colored subtractively. The results are said to show greatly improved definition and color-values.

Regal Productions are producing a programme of 8 Independent features in Consolidated's "Magnacolor" (Bipack) process, and a number of shorts, Spanish-language features, etc., have been made in Vericolor and other similar processes.

In the substandard field, Eastman's new "Kodachrome" 16mm. process (not to be confused with the earlier, 2-color process of the same name abandoned many years ago), is undoubtedly the outstanding achievement. This is a monopack, three-color subtractive process, involving the use of a multilayer film and intricate laboratory processing, but imposing no special requirements in taking or projection. It is understood that intensive research is under way to transform this reversal process to one which can be used professionally.

Almost simultaneously, Dufaycolor was introduced. This three-color process makes use of a ruled mosaic color-screen, and the material is available for 35mm. and 16mm. Cinematography and for many types of still photography. It is understood that some professional productions using Dufaycolor sequences have been made in England.

Stereoscopic ("Third Dimensional") Cinematography

Nothing of any commercial importance has been done in this field, though it is known that several studios, among which may be mentioned M-G-M and Universal, have conducted experiments with various processes behind locked doors. At the Fall Convention of the Society of Motion Picture Engineers, an experimental stereo process involving the use of polarizing spectacles similar to Eastman's Pola-Screens, was demonstrated. M-G-M released a Pete Smith novelty short-subject entitled "Audioscopes," in which a third-dimensional process securing the effect by complementary-colored images and spectacles, was used.

Film Standards

In the United States, five dimensional standards are well established. The professional standard of 35mm. film, with the so-called "Academy Aperture" and a standard .084" sound-track, is well known. In the amateur and non-theatrical fields, two 16mm. standards apply: the

Continued on Page 523

Problems of Controlling Correct Photographic Reproductions

SINCE THE INTRODUCTION of sound, it has become essential for any one engaged in the technical end of the motion picture industry to acquaint himself with the nomenclature of photometry. Characteristic curve, straight-line portion, toe, shoulder, gamma and latitude are common expressions exchanged and debated by cameramen and laboratory technicians, and became important practical units or factors in the discussion of photographic possibilities and results.

Still, however, while not underestimating the value of progressive technical education which lies in the popularization of certain fundamentals from the field of photometric science, it should not be overlooked that the conception of these laws and terms by the average person is not based on actual knowledge as to their evaluation, exact meaning and limitations, but is rather purely that of simplified tools or methods which are valuable in a practical way for the aid they offer in obtaining quicker results or greater accuracy and consistency.

As an example, we refer to the common practice of reading densities and plotting a sensitometric curve. This is a simple procedure performed by any one who is familiar with the manipulation of a densitometer and with the printed form of the graph paper. It is doubtful, however, that many would be able to explain the principle of this densitometer and its inherent limitations or to plot a density-log exposure curve of correct proportion on a plain sheet of paper, necessitating knowledge of the relation between density increase with exposure progression.

The above would justify attention to the fact that standardizing and mechanizing aside from its usefulness carries in itself the danger of releasing man from the necessity of creative thinking and substitutes a "taken for granted" attitude which undoubtedly would retard general progress. It is interesting in this instance to recall the enormous part played by the American radio amateur in assisting that industry to its present efficiency. Not satisfied with only turning a knob on a receiving set, the amateur participated in building his own equipment and thus accumulated experience and knowledge that was utilized with great success by the commercial manufacturer.

After years of experience in the manufacturing of raw film and also in consumption in the practical field, the writer is aware that the consumer, represented by the camera and laboratory men, should know these products even better than the manufacturer, who in this case sells his merchandise practically without visual inspection. It is, therefore, equally logical that a large proportion of creative advice towards improvement of the film product should be contributed by the practical man on the basis of both his intimate knowledge of products and his consciousness of the consumers' current problems and future needs.

Fortunately, this has been the case and has resulted in much constructive advice which has been instrumental in assisting the film manufacturer to improve the quality of his products. The writer feels, however, that the effectiveness of the camera and laboratory men in this instance could be greatly increased if both had a deeper and clearer technical conception of the photographic principles underlying their practical experience and daily work.

The following articles are written with these thoughts in mind and might aid one or the other in widening his understanding of photographic terms and laws.

by
Doctor Herbert Meyer, A.S.C.

The fundamental law governing faithful photographic reproduction of natural objects is expressed by two equations:

1. $C_n \times C_p = C_o$.
2. $C_o = 1$.

Wherein C_n represents the contrast or gradient of the negative emulsion, C_p that of positive material, and C_o the overall contrast in the final print.

It follows from these equations that:

$$C_n \times C_p = 1.$$

A variation of this law is better known in laboratory practice which quotes:

$$\begin{aligned} \text{Gamma Negative} \times \text{Gamma Positive} &= \\ \text{Overall Gamma,} & \\ \text{or} & \\ \text{Gamma Negative} \times \text{Gamma Positive} &= 1. \end{aligned}$$

This version plays a substantial and well-known part in the field of sound recording and reproduction especially when applying the variable density method and straight line recording. In pictorial photography, however, this simplified equation is practically useless as it does not answer the question of exact reproduction for the reason that gamma refers to the straight line portion exclusively, while a considerable part of the photographic reproduction utilizes the curved-toe portion of the positive film as it is necessary to render clear highlights in the finished print. Hence, it is essential to apply the general equation as given above in which the overall gradient equals unity and which takes into consideration every part of the gradation including the curved portions.

In laboratory practice the terms and utilization of gamma values have been introduced principally as a means of controlling the constancy of development and developing solutions. Experience, however, has taught the laboratory man not to rely on gamma values alone, but also to check and protect uniformity of density level in development by reading individual density tabs in connection with every gamma test, one of which, as a rule, is a low density located in the curved-toe section of the characteristic curve as applied to positive film. These tests, no doubt, serve as a means of not only keeping the gradient of the straight-line portion constant in the developing procedure, but also of preserving the shape of the toe section which in combination represents a fairly accurate method of protecting

Continued on Page 524



ARTHUR EDESON, A.S.C.

An Etcher of Character

---is Arthur Edson

by
Harry Burdick

SOME TWO DECADES BACK, Arthur Edson was holding enviable rating in the fore-rank of photographic portraitists of the nation. When he graduated to the wider realm of cinematography, he took with him a priceless heritage—the well-nurtured gift of pictorial character delineation.

This sharpened talent has stood him in good stead throughout his many cinematographic adventures. It is the underlying fundamental of his camera conceptions. It directs him to lens characters instead of actors, dramatic action rather than individual posturing before sets. It goes far to explain why Edson has been entrusted with more million dollar productions than any other practitioner of screen camera craft.

It provides explanation, also, for the subtle charm and

the epic sweep of artistry that permeates his every screened work. It accounts, too, for his amazing versatility, the flexibility of his camera technique to accommodate dramas of so widely divergent content as "All Quiet on the Western Front," "Frankenstein," "Mutiny on the Bounty," "In Old Arizona," "Ceiling Zero," to itemize a few works of differing concept.

He has placed on celluloid an astounding variety of stories. Each new assignment, it seems, takes him into uncharted paths of endeavor. But regardless of the scope or nature of the plot to be unfolded, his underlying talent at true and sincere character portrayal prevails.

There is no betraying earmark of sameness nor monotonous stereotyping to his steady stream of successful screenings. His treatments are as varied as the stories themselves; each in close keeping to the particular narrative. Indeed, story wholly governs his procedure.

Blessed with a deep story sense and drama valuation, he goes about his work much as would a novelist or playwright, but with camera rather than pen as his vehicle of expression.

Establishment of exact mood paints in his emotional atmosphere and level. Then he deftly captures character and characters on his negative, recounting his dramatic tale through precise development of character as the story carries on to climax.

He gives painstaking attention to detail, before and during actual shooting. Days are devoted to thorough consideration of the cinematographic mechanics involved. This intense preparation done, he calmly and patiently "makes pictures."


His recent "Mutiny on the Bounty" is instance of his deliberate insistence on technical and dramatic perfection. This historical opus was twenty weeks in the making. It presented cinematographic difficulties in quantity to contribute jitters to the most poised artist. It was the most difficult from physical obstacles of any picture to his record.

Shooting was done in a land-locked bay at Catalina. As no land must show and so destroy the illusion of a ship far at sea, he could direct his camera only in one general direction. Now came the disturbing element. The good ship, "Bounty," had to be in position into the wind so that its sails might be filled. And the wind, day to day, as sea breezes will, changed about in prankish fashion and would never blow in the same direction two days running; or even throughout a full day, for that matter. Hence, Edson encountered one of the toughest lighting problems on record. He would have blinding blue skies, or gray, foggy skies. The light and color of the sea, of course, changed correspondingly. He had white sails against white and gray skies. He had characters to light and costumes to convey. In addition and just to make his cup of troubles full to the brim, he was using not more than a 40mm lens throughout, that the "Bounty" might seem small as possible.

Because of all the confusing factors, it became one of the most exacting filtering undertakings one can imagine. How well Edson solved his myriad technical problems and emerged triumphant over variable elements is demonstrated by the accolades of high praise from reviewing critics sitting before his projected photography.

From these puzzles of purely nautical nature, he turns to his current production, "Ceiling Zero," a Warner Brothers epic treating of air mail dramatics. Throughout this document, menace is furnished by fog; thick, soupy fog always

Continued on Page 526



Innovations Mark New 20th Century Silent Camera

COMBINING many radical innovations in design with well-considered practicality, a new silent camera has been developed by the cinetechnical staff of the Twentieth Century-Fox Studio. At first sight, the camera appears essentially to follow the accepted school of American studio-camera design: but upon closer inspection it becomes evident that although all of the accepted components are present, they are assembled in a decidedly unconventional manner, and further examination reveals a definite, practical reason for each departure from orthodox practice. The obvious question about any silent camera is answered, in the case of the Twentieth Century Camera, by the statement that it has already been used on an entire production, ("Show Them No Mercy") unblimped, and at times within two feet of the microphone.

The development of the new camera might be described as something of a community project. Conceived and built under the guidance of Grover Laube, head of the Studio's cinetechnical department, patent-office records list, in addition to Laube, Charles Melvin Miller, Robert C. Stevens and Edward Albert Kaufman, all of the studio's precision cinetechnical shop, as the actual inventors of the camera; but they are unanimous in paying tribute to the cooperation and practical suggestions received from Camera Executive Godfrey J. Fischer and his staff of Cinematographers. It is a remarkable evidence of the spirit prevailing at the studio that the research and development work of this project was undertaken privately by these individuals, and that save for the actual materials used, the completed camera had no charge against it when it was presented to the company.

The general layout of the Twentieth Century camera adheres essentially to conventional American practice. That is, a four-lens turret is used, a durable metal box houses the camera mechanism itself, and is surmounted by

by
William Stull, A.S.C.

dual, external film-magazines of 1,000 foot capacity, while the driving-motor is mounted at the rear. Access to the mechanism is through a door on the left-hand side, at which side is also mounted a finder interlocked with the focusing mechanism and automatically correcting for focus and parallax.

The camera housing, however, is cylindrical in shape, rather than square. This is due not to any intention to be causelessly novel, but to the fact that this shape is best suited to the rotating focusing shift employed. The cylindrical case is mounted on a yoke-shaped base, and in focusing rotates on the axis of the main shutter-shaft. This rotation brings the focusing microscope into place between the lens and a fixed eyepiece at the rear. Both of the bearing surfaces upon which the housing rotates are completely enclosed, and thus protected from dust and

grit which can not only cause wear, but at times obstruct the full movement of an unprotected shift. Positive, cushioned stops limit the travel of the shift, and prevent both jarring and misalignment. The eyepiece, incidentally, is adjustable to suit the eyes of the various members of the camera crew, and is calibrated for easy adjustment. A secondary advantage of the rotating focusing shift is the fact that the movement may be reloaded or inspected by the assistant without interference with the focusing operation.

A conventional disc type shutter is used, with an aperture of 200° . The movement, which employs registering pilot-pins, is characterized by a remarkably even action. This movement was designed only after exhaustive analysis of the take-down mechanisms of the principal types now in use. Fig. 1 shows curves representing the velocities of the take-down pins in the new camera contrasted with a composite curve representing an average of several types now in general use. It will be noted that although the take-down of the Twentieth Century camera takes place in a relatively brief period, it is uniform throughout, and does not attain at any point in the cycle an unduly high velocity. The peak velocity is approximately 73 inches per second, while in some conventional designs the velocity not only reaches a peak of 98 inches per second, but peaks very sharply. The take-down pins have absolutely no vertical movement at the moment of engagement and disengagement, though in some commercially used types the pins enter and leave the perforations while still possessed of considerable vertical velocity—i.e., moving in an arc rather than straight into and out of the perforation. Due to these characteristics of straight-line engagement and disengagement and uniform acceleration, it has been possible to shape the take-down pins very accurately, giving both the moving pins and the registering pins a very precise fit in the perforations, and assuring the maximum of accuracy and steadiness.

Silence is secured by this uniform action, by minimizing gearing and the weight of moving parts, and by giving the film as nearly free a path as possible. No sound-proofing other than the conventional black velvet lining is used in the camera, the aim of the designers having been to prevent the cause of noise, rather than the effects. Magazine noise is minimized by affording the film free passage, eliminating contact between the edges of the film and the walls of the magazine. At present, specially rebuilt magazines of conventional type are fitted, but an improved type is being developed. A special locking spool is used, fitted with an ingenious, but easily operated lock which holds the spool rigidly to the shaft. The take-up drive is by belt from an internal clutch. The varying size of the film-roll is compensated for by this clutch, rather than by slippage of the belt. For this reason, when the camera is in operation, it is said that the action of the take-up drive appears deceptively slow.

Provision has been made to use a wide variety of standard driving motors. The present equipment is powered with a standard 1440 R.P.M. synchronous motor, the stator field of which may be shifted to synchronize with the projectors used in background-projection process cinematography.

The monitoring finder is of the conventional type,





Fig. 1


interlocked with the lens-focusing mechanism to correct for focus and parallax. In the latter movement, however, it differs basically from routine practice. Instead of securing the parallax-compensating adjustment by swinging the entire finder on an arc, the compensation is made by a lateral movement of the finder-lens, which may be roughly compared to the sliding front-board of a still camera. The designers state that this method eliminates a number of inaccuracies inherent to the conventional pivoted compensating movement. A release button on top of the finder throws the lens back into normal (or distant-focus) position when it is desired to make a quick check of the distant field covered, as in a follow-focus shot.

Due to the compactness permitted by the rotating focusing shift, the finder is mounted in remarkably close proximity to the photographing lens, further simplifying the problem of finder-parallax. Due to the close relation of the finder and the photographing lens, a specially wide sunshade is used, shielding both objectives.

The focusing control follows the pattern familiar at the Twentieth Century-Fox studio; a quadrant and lever mounted on the left-hand matte box arm carrying the focusing scale and control.

An important feature of the new camera is the fact that a single focusing scale suffices for all lenses. This

Continued on Page 520



Complete Laboratory in One Unit

Editor's Note: Believing that a communication just received from George Schneiderman might strike a responsive note among many other cinematographers who possibly have encountered the problem faced by Schneiderman, we are printing his letter on a "One Man Laboratory," which he has discovered. Schneiderman has been in the motion picture business for more than 25 years in the photographic branch of the industry. For fifteen years he was with John Nicholas in the New York Universal Film Co. laboratories. He erected the first laboratory in the tropics, constructed in Kingston, Jamaica, in 1915. He operated the release print laboratory for Fox Film Co. in New Jersey from 1915 to 1917, and was in charge of Fox West Coast laboratories from 1917 to 1923. Since that time he has acted as a first Cinematographer with the Fox Film Co.

by
George Schneiderman, A.S.C.

did not possess the efficiency that is now being enjoyed by all makers of pictures.

"In my intensive search to find a machine that would meet my requirements, I feel I was fortunate in locating Hugh H. Gwynne, who has, in my opinion, designed and built the only practical developing machine in existence for my purpose and possibly the use of many others who require small but efficient units, in fact a machine that can be operated by one man, which gives it its trade name of "One Man Laboratory."

The following specifications will give any experienced cinematographer or laboratory man a more comprehensive idea of the utility of this "One Man Laboratory."

"Developing time for positive is adjustable to run from one to four minutes, manufacturing from five hundred to two thousand feet per hour. Negative film has a capacity from two hundred to nine hundred feet per hour.

Continued on Page 525

"AS YOU ARE already aware of my intentions to make pictures in foreign countries where laboratories are not established, it was necessary for me to either build or have built a developing machine for the processing of my film.

"I gave considerable thought to the possibilities of going back to about fifteen years, to what is known in the industry as the rack and tank development. This, however, in view of the fine and great developments made in the industry in all of its branches, seemed like saddling a venture not only with a hardship, but with something that

Destroying Pompeii— in Miniature

by
Edwin G. Linden, A.S.C.
as told to
Walter Blanchard



Enlarged from one of Linden's tests. The temple and city are on one glass, the volcano on another, while the smoke is projected. In this test, the smoke was 1/32 of an inch out of correct alignment.

IT IS OBVIOUS THAT to be of any value to a production, miniatures and other special-process or "trick" shots must look real, lifelike and natural. Equally important, though not so universally realized, is the fact that they must also have feeling, mood and balance. Special-effects scenes must maintain the same artistic standards as the production into which they are cut; in other words, the special-process cinematographer must make his scenes a perfect match for those of the production cinematographer. The more thoroughgoing this cooperation is, the better will be both the process scenes and the production as a whole.

Technically, of course, special-effects work is based on paying infinite attention to details. One of the most important of these details is absolute rock-steadiness in every phase of the shot. Especially where there are a number of exposures superimposed to form one scene, the slightest "jiggle" or movement in any one exposure will ruin the entire shot. We had one scene in "The Last Days of Pompeii"—the long-shot of the destruction of Pompeii by Vesuvius—which required seven exposures; two were made at six times normal camera-speed; one at ten times normal; three were stop-motion exposures; and the seventh was a normal 24-frame per second shot. In any of these exposures, camera-movement, or even vibration, which would pass unnoticed in a normal shot, would have ruined the entire job.

Due to the extreme care with which the cameras were conditioned, tested and tied down, and the film handled, we were fortunate in having to make but one "take" of this shot. As an illustration of the super-critical pains which must be taken in this sort of work, I might mention that we had to keep people from even walking across the stage-floor while we were shooting! Ordinarily, a well-constructed stage floor would be regarded as a pretty solid piece of construction—but our tests showed that ordinary, middleweight footsteps walking across the floor produced enough vibration to endanger our shot. Therefore, when we actually made the scene, we had the stage roped off so that nobody but the crew actually working the set could approach within thirty feet of the cameras.

One of the first tasks in making this scene was to film the smoke which you saw (or didn't you?) rolling out of the crater of Mt. Vesuvius, and the threatening clouds which frowned over the city during the eruption. The smoke and the clouds called for rather different effects,

so they were made separately. In the case of the smoke, we photographed it in several different ways, at speeds ranging from four to twelve times normal, and in shades ranging from black to white, and from just a thin, lazy wisp to a magnificent roaring volume.

Thousands of feet of negative were exposed on smoke alone (you know at 700 feet or more per minute, it doesn't take long to run up a lot of footage). Then we would get into a huddle in the projection-room and pick the best takes to use in our composite shot. You'd be surprised how much argument there is in just smoke!

The burning boat in the foreground in some of the scenes was not a miniature, but like the foreground water in other shots, was made normally, at San Pedro.

The city itself was largely done on glass, while Mt. Vesuvius was another glass.

Some of the flames, too, were high-speed miniatures.

In bringing the whole thing together, we had a rather intricate problem. For different sequences, the city of Pompeii had to be photographed with varying effects, representing day, dusk and destruction. The first required a bright, sunshiny effect, with the foreground water calm and bright, and the smoke from Vesuvius rolling lazily, almost imperceptibly. Then the appearance had to be changed to dusk, with lights and a glow from the volcano. Finally, the scene had to be changed entirely; Vesuvius, as you remember, had to do its stuff. The city had to take on a murky hue, the foreground water had to do some tossing about, and over the city a cloud of ashes was requested by the Powers that Be. (Mind you, the ashes must look like ashes—but mustn't obscure the picture!)

In assembling these various ingredients, the city and the volcano, which were glass paintings, were lined up in their proper relation. The smoke, the clouds, and the foreground-water were projected into their proper places by stop-motion background projection, and the flames—well, some of them were also projected in, and others were painted in on yet another glass, carefully lined up with the others. Of course, partially-silvered mirrors were employed in some instances, to simplify the physical group-

Continued on Page 522

Innovations Mark New 20th Century Silent Camera

Continued from Page 517

is made possible by a unique lens-mount, the invention of Messrs. Laube and Kaufman. Essentially, this lens-mount consists of three collars: the outer collar, attached to the camera, the inner collar, attached to the lens, and an intermediate collar which acts as a cam to provide the focusing movement. The lens itself does not rotate, but moves straight in and out. It is supported firmly at both ends of the mount on sliding bearings: the inner end being supported by the inner end of the inner, or lens-carrying collar, fitting into the outer collar, while the forward end of the collar is supported by several small, renewable bearings extending through the intermediate collar.

Cam-shaped slots are cut in the in-

termediate collar, and in them run tapered rollers, one set of which is anchored to the inner collar, the other to the outer collar. Therefore, when the intermediate collar is rotated, the lens in the inner collar is moved straight forward or back, without rotation. The rollers are pressed into their respective slots by spring pressure, automatically compensating for wear. The cams are cut so that regardless of the focal length of the lens in question, rotating the intermediate collar to any given degree will bring any lens to a focus at the same point. This obviously permits the use of a single, remotely located focusing control and scale for all lenses. A simple mechanical linkage interconnects the lens-mount, focusing control and finder. No supplementary cams are necessary between the focusing mechanism and finder, and there are no accessories to be changed when lenses are switched.

Regarding the development of the camera, Laube says, "In creating this camera, we have tried not only to produce a successfully noiseless camera, but to produce a more perfect photographic instrument as well. One which will meet today's known problems fully, and which will be prepared to cope with every one of tomorrow's needs insofar

as we can foresee them. In the history of cine camera-design, there are certain designs which stand out like beacons, plainly marking the course of cinematographic progress. Following Eastman's invention of celluloid film, and Edison's invention of the Kinetoscope, there ensued a period of rather aimless pioneering: almost any camera that would make a moving picture was accepted, regardless of how carelessly it was designed, or how crudely it worked. About 1910, Bell & Howell introduced scientifically standardized design, and a new note in precision engineering. Roughly a decade later, the Leonard-Mitchell design answered the call of the times with a new, faster-working camera. It is significant that both of these designs have endured, with only minor modifications, until today. Though their designs were laid down ten and twenty-five years ago, these cameras are still photographing our pictures today. They are at once a challenge and an inspiration to any man who undertakes the design of a professional camera today.

"In planning the Twentieth Century Camera, we have striven to strike an equally foresighted note. A silent camera is in itself a worth-while development: but if it can offer no real advancement beyond the mere absence of noise, it cannot be considered a really enduring achievement. Eliminating noise will automatically free Cinematography from the physical shackles imposed by quarter-ton camera-blimps, and speed up production, taking care of today's immediate needs, but leaving unanswered the needs of the future. Putting it another way, we are getting along adequately enough with our present repeatedly rebuilt cameras and blimps; each new blimp-design, too, tends toward easier operation and lighter weight. Eliminating the need for blimps would unquestionably facilitate production to the extent of permitting economies which would quickly offset the initial investment in new equipment: but if the cameras, as photographic instruments, did not yield better photography, and make provision for meeting such future needs as we can foresee, we would not be essentially any better off than if we continued using present-day equipment.

"We have tried to fulfill both of these requirements in the Twentieth Century Camera. Silent operation, we have definitely secured. The camera does not need any soundproof covering at any time. This, together with the general layout of the apparatus, makes for faster—and therefore more economical—operation. Instead of a crew of four men needed to move a 400 pound blimped outfit, a single man can shoulder this 82-pound camera and move it as easily as only pre-talkie equipment.

FRIED 35MM

LIGHT TESTER

In use by Hollywood Laboratories.
Price Complete \$550.00

Fried Camera Co.

6150 Santa Monica Blvd.
Hollywood, Calif.

Also manufacturers of 16mm
printers and testers.

ALL TYPES OF Cameras and Accessories for SALE and for RENT

We Have on Display the Largest Stock of New and Used Modern Camera
Equipment and Accessories of any Camera Supply House in the World!

Eastern Representatives

MITCHELL CAMERA CORPORATION

HARRISON FILTERS — FEARLESS PRODUCTS

MOVIOLA FILM EDITING
EQUIPMENT

We only sell equipment that
we can guarantee. Get our
Price first!

FRANK C. ZUCKER

J. BURGI CONTNER

**MOTION PICTURE CAMERA
SUPPLY, Inc.**

723 Seventh Ave.

New York City

Telephone BRyant 9-7755

Cable Address: Cinecamera

CLEAR GAIN

THE photographic quality of Eastman Super X Panchromatic Negative is truly outstanding. Equally important, however, is the fact that the pronounced improvement which has been achieved involves no compromise. It does not mean the sacrifice or impairment of any other desirable or essential quality. It is clear gain for the industry, and for the public. Eastman Kodak Company, Rochester, N. Y. (J. E. Brulatour, Inc., Distributors, Fort Lee, New York, Chicago, Hollywood.)

EASTMAN *SUPER X*

PANCHROMATIC NEGATIVE

Attention . . . Foreign Producers!

Ultra Silent Camera

No Blimp Necessary

DEBRIE AT SACRIFICE**New Type SUPER PARVO DEBRIE**

Has built-in motor, automatic dissolve, pilot pins and anti-buckling device. Four 1000-ft. magazines—40mm, 50mm and 75mm lenses—Debbie friction tripod and new type Debbie finder. Leather-covered carrying trunk and tripod cover. It's the latest type equipment . . . like new!

*Thoroughly Guaranteed***SACRIFICE . . . \$2,250****MOTION PICTURE
CAMERA SUPPLY, Inc.**723 Seventh Avenue New York City
Cable: "Cinecamera"

Destroying Pompeii---in Miniature

Continued from Page 519

ing of all these various elements. Obviously, the shot had to be lined up very carefully, and many tests made to make sure that the smoke didn't roll from the wrong place, or that some other misalignment didn't occur.

Finally, in several of the shots, people were added in the foreground by the travelling-matte process—and the shot was complete, having passed through half-a-dozen or more different cameras.

One of the finest examples of the miniature-builder's art was the "Temple

of Jupiter," constructed under the supervision of Willis O'Brien by Gus White and his assistants. In the background, behind the temple (which was an exact reproduction of the original, according to the most authoritative reconstructions), was Vesuvius, belching forth its fire, lava and ashes. Overhead, the clouds of ominous-looking smoke. Throughout the city, the burning and smoking buildings. And finally the crash and destruction of the temple.

This was one of those nerve-racking shots, for it had to be made—and made right—at one take. The slightest slip on the part of any one of the twenty men who worked this set would mean weeks of hard work rebuilding and re-shooting the scene—not to mention thousands of dollars extra expense to the studio.

We made test shots of all the effects except the actual crash of the temple—the most important effect, and the only one we couldn't test. Thanks to the efficiency of Harry Redmond's crew of "effecters," only minor changes were needed. A little less smoke here, a little more flame there, and so on. Then the four cameras were again tested for steadiness, for here, too, steadiness was a prime requisite, as chariots, horses, and people (real ones!) had to be processed in later—and even an earthquake couldn't explain a background that jiggled while the foreground didn't.

The tests are projected, and the final minute changes are made.

"Zero hour" is at hand.

The order, "Hit 'em!" is given. The lights blaze on. Flares and fire-pots are lighted. Hundreds of smoke-pots are fired electrically. Everything is ready.

"Camera!"


"Let 'er go!" The rocking motion of the earthquake starts—the wires start the building to crumbling, and "go" she does.

"A-a-ah!" All hands sigh with relief. Perfect the first time!

Did it look real? There were some who saw the "rushes" who wouldn't believe it was done in miniature!

The scene in the arena, in which the Colossus crumbles and falls after the start of the earthquake was another thrillingly difficult scene. It was not "done with mirrors," as some reviewers have expertly stated, but was a combination of a full-sized arena set, with real people and horsemen, a miniature arena, glass painting, miniature projection, and a life-size breakaway Colossus which was photographed at high

Revolutionizing Studio Lighting



Junior
(2000 Watt)

**SOLARSPOTS**

Senior
(5000 Watt)

The Perfect Photographic Light

The first studio lighting unit designed exclusively to meet the requirements of photographic lighting. For the first time, high illuminating power and smooth wide-range light-distribution are combined in a single unit. The SOLARSPOT may be concentrated to an intense spot-beam, or diverged to a 44° floodlight spread without producing "hot-spots" or "dark spots." The beam is at all times ideal for photographic illumination.

Mole-Richardson, Inc.

941 No. Sycamore Ave., Hollywood, California

Cables: "Morinc."

speed. The task of merely combining these shots into a homogeneous composite is an intricate problem of special-effects trickery in itself.

How were all of these earthquake and eruption effects made so lifelike? Well, here in California we have a certain amount of first-hand information about earthquakes, even if we are a bit shy on volcano lore. The volcano part, however, we perfected through careful study of scientific descriptions of actual eruptions, and analysis of films of volcanic outbursts, including "Krakatoa," and newsreel scenes of actual eruptions of Vesuvius. However, we had to take dramatic license in many respects, for a real eruption is such a grimly slow-moving thing that it lacks the thrilling "punch" demanded on the screen!

Making these scenes is almost as gruelling as living through a real eruption—though for an entirely different reason. With so many tiny details which may go wrong and spoil a scene which cannot be re-taken, the nervous tension is terrific. After living through "The Last Days of Pompeii," following "Kong" and "Son of Kong," I can heartily sympathize with the special-effects "ace" who, after successfully filming a miniature in which a \$50,000 scene was made in 20 seconds, had a nervous breakdown and spent a month in a sanatorium!

familiar 16mm. for silent films, and the R.C.A. 16mm., with one row of perforations eliminated and the edge of the film utilized for the sound-track, for sound-on-film. Two standards are known in the 8mm. field: Eastman's original type, in which specially perforated 16mm. film is split lengthwise after processing, resulting in a projection-standard of 8mm., single perforation film; and the newly-introduced Bell & Howell pre-split 8mm. film, in which both camera and projector use single-perforation stock 8mm. wide.

Abroad, in addition to these standards, several others are found in the substandard field. Among these are the Pathe Rural 17.5mm. non-theatrical standard, upon which a sound-track is sometimes added by suppressing one row of perforations; a 16mm. sound-film in which both perforations remain, and sound-track and picture are in the same relation as in standard 35mm. film; and Pathex 9.5mm. amateur film, which is center-perforated.

Sponsored by the Academy of Motion Picture Arts and Sciences, a movement is under way to standardize release-prints on 2,000 ft. reels. Despite the

cost of the new equipment involved in theatres and exchanges, important economies are anticipated, and several of the major distributing-firms have agreed to make such a change for domestic releases after the first of the year.

Sound

A general improvement in sound-quality has been noticeable.

Both Western Electric and RCA have developed so-called "push-pull" recording and reproducing methods productive of more natural quality, lessened ground-noise, and a much greater volume-range. The system used in conjunction with Western Electric recording was developed by Douglas Shearer, A.S.C. and his associates at the M-G-M studio, where it is in use.

In consequence of these high-quality recording methods, it is understood that several major studios are supplying two types of release-prints: one carrying the "push-pull" sound-track, for theatres equipped with reproducers and amplifiers capable of reproducing from such

TAYLOR-HOBSON COOKE

SPEED-PANCHRO

LENSES FOR TODAY'S LIGHTING AND COLORS

A New 2¼ inch F 1.3 to supplement the famous F 2 Speed-Panchros

And now the extremely fast F 1.3 with the same full chromatic correction as the F 2 series, providing beautifully crisp image under most adverse lighting conditions.

★ Taylor-Hobson Cooke F 2 Speed-Panchros are universally preferred for black-and-white and for color work, because they are the most perfectly color-corrected lenses ever formulated, giving not only maximum color correction for today's production conditions, but also exceptional correction for all other aberrations. Eleven focal lengths, 24 to 108 mm.

Write for full description


BELL & HOWELL COMPANY

CHICAGO—1848 Larchmont Ave. • NEW YORK—11 West 42nd St.

HOLLYWOOD—716 North LaBrea Ave. • LONDON

World Leaders in the Design of Professional Cinematographic Equipment





NEW IMPROVED CINEGLOW

3 ELEMENT

Recording Lamp

- Longer Life
- More Exposure
- Uniform Quality

Used The World Over

Write for prices
and literature.

Blue Seal Sound Devices

Incorporated
723 Seventh Ave.
New York, N. Y.

a track, and a re-recorded version for theatres with older equipment.

An interesting development was the Miller-Phillips Mechanographic recording system. This uses a stylus to cut a mechanical record in an opaque coating on the film, which record can then be either re-recorded mechanographically or printed photographically for releases. Greater resolving power and consequent improved quality are claimed.

The Berndt-Maurer Corporation introduced a new type of oscillograph (galvanometer) recorder which may be substituted for a glow-lamp, and produces a Variable Area track.

Considerable use was made of Vertical Cut ("hill-and-dale") disc recording for recording musical selections, and some studios used acetate discs similar to home-recording phonograph records for immediate playbacks.

The renewed interest in color cinematography brought the problem of high-quality film records on color prints to the fore.

Standard Sound

16mm. sound-on-film appeared at last to be wresting substandard supremacy from the more unwieldy sound-on-disc. A number of new 16mm. sound-on-film projectors—all using the RCA single-perforation standard—were introduced. Among them are such familiar names as Bell & Howell, Ampro, Victor, DeVry, and the like.

Bell & Howell announced the formation of a 16mm. sound-film library, while trade papers carried reports that British and other producers were reducing their 35mm. theatrical releases to 16mm. very quickly after general release of the 35mm. version. A noted Hollywood Producer, Edwin Carewe, formed a company to produce religious features for 16mm. non-theatrical release.

Bell & Howell perfected an excellent reduction printer for optically reducing sound-tracks to 16mm., and DeBrie, of Paris, entered the American field with reduction printers, developing machines, and other substandard apparatus.

Projection

Professional projection problems seemed heightened by the increase in density, and the consequent need for more intense light, resulting from natural-color films. Partly to meet this need, the National Carbon Company has developed several new types of projection carbons, and lamp manufacturers, optical firms, and the like have contributed advances in projection-lamps, condensers and lenses.

In the substandard field, a general increase in the power of projection-

lamps was evident. 16mm. projectors of 1,000 watts were introduced, and 8mm. projectors of 300 and 400 watts placed on the market.

With the increased use of 8mm. cameras, a new interest in projectors capable of interchangeably projecting 8mm. and 16mm. film became evident in many quarters.

Laboratory Methods

The commercial application of the involved processing required for Kodachrome 16mm. color-film, which is stated to involve more than 35 separate operations, was undoubtedly one of the greatest achievements in the laboratory field.

Competition from studio laboratories appears to be forcing the modernization of commercial plants.

The Eastman Kodak Co. introduced the "Argentometer," a device for determining the silver content of hypo solutions. A buffered sodium sulfide solution is added to a standard quantity of the solution to be tested, which is then placed in the argentometer, in which the altered transmission of the solution alters the reading given by a microammeter connected to a photronic cell.

Several laboratories have been experimenting with photocell-densitometers. In some instances, such devices are understood to be used commercially controlling the processing of sound-track.

Art Direction

"Becky Sharp" proved that much of the success or failure of natural-color films will depend upon intelligent art-direction, and it is generally conceded that the future of color rests on the shoulders of the Art Directors and the Cinematographers.

Problems of Control

Continued from Page 514

the consistency of contrast.

The problem faced in photographic reproduction can be condensed to that of creating a visual sensation in the finished print identical to that conceived by the eye when observing the original object. This sensation is governed principally by the amount of brightness as a whole and by the brightness differences which are identical with contrasts. While it is relatively simple to control photographic results by exposure and processing sufficiently to satisfy the request for identical brightness to the eye in the finished print as



1515 Cahuenga Blvd.,
Hollywood, Calif.

Phone: GLadstone 2404

Recording Machinery Hollywood Motion Picture Equipment Co.

645 Martel Ave. Cable Artreeves
Hollywood, California

FEARLESS CAMERA CO.

Velocitor Camera Dollies, Camera Blimps, Camera Motors, and complete camera accessories and equipment.

8572 SANTA MONICA BLVD.,
HOLLYWOOD, CALIF

in the natural object, the problem of matching brightness differences or contrast in the final photographic reproduction to that conceived by the eye from the natural object is of an extremely complicated nature.

The solution lies in the fulfillment of the above given equation which calls for an overall gradient equal to unity.

In analyzing this equation and applying it to existing practical conditions the following statements must be thoroughly understood. In every laboratory the positive gamma is a constant factor for the reason that faithful sound reproduction depends upon fulfillment of the same law controlling overall gamma. Thus the product of the negative gradient multiplied by the positive gradient and also the positive gradient itself are constant, that is, they are fixed values not eligible to any alteration of great proportion.

This fact places an enormous responsibility on both the cameramen and the negative developer as the negative gradient must be of a definite uniformity, the maintenance of which is a difficult task due to the many variables introduced by the present methods of photographically recording a motion picture.

The next article offers an analysis of these difficulties which comprise the principal practical problems of the cameraman.

Complete Laboratory in One Unit

Continued from Page 518

"The operator has accurate gauging of his developing time by a mechanical and manual control.

"The chemical solutions as for temperature and mechanically controlled refrigeration and thermostatic.

"Agitation of the developing solutions is done by a circulating pump.

"All water and moisture is entirely removed from the film after leaving the last wash tank and arriving in the dry box. This is done by an ingenious mechanical absorber.

"The entire mechanical construction of the machine is built from high-alloy non-corrosive, non-magnetic steel.

"The machine is completely insulated to aid temperature control.


"The phenomenal part of this machine is that it requires little space. The entire set-up can be installed in a room twelve feet long and six feet wide.

"The dimensions of the Junior model are:

"Ten feet, six inches long, by five feet, nine inches high, by three feet wide.

"Shipping weight will not exceed one

DeVry Sound Camera for Single or Double Recording and Bi-pack Color Photography




Professional Results
with Light, Easy
Handling

Herman A. DeVry's well known genius for simplification was never better illustrated than in this great piece of cinematographic engineering. There is no room here to go into details. These will be furnished on request. Suffice it to say that here is a studio sound and picture recorder, incorporating such masterful engineering that it is faster in setting up and operation, for studio or news reel work than any camera made.

Famous DeVry "A" News Reel Camera

—Now with 24 speed to synchronize with sound. Can now be furnished with a new high speed shutter and fast lens — ideally suited for quick action shots on location, which later can be enlarged for lobby displays, and other advertising.

Meanwhile, the DeVry "A" continues to hold its grip on the affections of the News Reel Fraternity the world over — especially the men in the front line who travel light and fast and must have reliable equipment.



DeVry Combination Super-Speed Camera for Both Movies and Action Stills.

HAVE YOU INVESTIGATED—The DeVry 16mm Sound Camera—The DeVry Sprocket Intermittent 16mm Sound Projector—The DeVry Theatre Sound Projector—The DeVry 35mm Portable Sound Unit and the new DeVry Clock Spring "Reeis Eternal" up to 1600 ft. in 16mm size, and 2000 ft. in 35mm.

HERMAN A. DeVRY, Inc.

Manufacturers of the Most Complete Line of Motion Picture Equipment in the World.

1111 CENTER ST.

Distributors in all principal cities.

CHICAGO

• MOVIOLA •

FILM EDITING EQUIPMENT
Used in Every Major Studio.
Illustrated Literature on request.
MOVIOLA CO.
1451 Gordon St. Hollywood, Calif.

thousand pounds, or five and one-half marine cubic tons.

"The machines will be distributed through the Premier Motion Picture Equipment Company, located at the factory of the Gwynne, "One Man Laboratory," Developing Machine Company, 8226 Santa Monica Boulevard, Hollywood.

An Etcher of Character

Continued from Page 515

seeking to clutch at men who dare fly and to claim them for its own. Every scene shows this atmospheric villain.

Interior scenes, of which there are many, depict a normally aired room but with the clinging fog constantly menacing just outside wide windows. Here again, lighting requirements were far from elemental. These scenes had to be lighted twice; once for the clear interiors and again for the murky exterior.

Handling of the fog itself presented intricate mechanical difficulties, mainly in keeping the fog out of the interior sets and outside, where it belonged properly.

A series of fans handled the outside fog satisfactorily, but the thin vapor insisted in penetrating the interior set. Then was evolved an ingenious series of air-pumps leading into the inside set, setting up just sufficient air circulation to keep the fog outside but not interrupting its normal action in the open air.

To complicate further the conditions, beams from a revolving beacon penetrated at regular intervals foggy exterior and lighted interiors.

Edison combines within his stocky, pleasant person a remarkably exhaustive knowledge of cinematographic machineries with his talent of pictorial dramatic revelation. At his home, his private laboratory gives him opportunity for extensive experimentation. There is little in the great field of photography and its allied subjects that he is not, from first-hand handling, surprisingly familiar with.

But the finest of tools must be properly used, and it is with their use rather than the instruments themselves that Edison is most concerned. Technically, his photography is correct. With this background of laboratory perfection, he goes forward into the field of showmanship. A keen student of audience reaction, he never hesitates to employ proved expedients to heighten dramatic effect. He is adept at what may be termed cinematographic change of pace; of subordinating one sequence that the following incidents may burst forth in accented strength.

Everything Photographic

for Professional and Amateur

New and Used, bought, sold, rented and repaired. Designers and manufacturers of H. C. E. Combination lens shade and filter-holder for any size lens.

Hollywood Camera Exchange

1600 Cahuenga Blvd., Hollywood

Tel: HO 3651

Cable Address: HOCamex

Send for Bargain Catalog


TRUEBALL TRIPOD HEADS

OF SPECIAL ALLOY
LIGHTER WEIGHT

The Same Efficient Head

For follow shots, known for their smoothness of operation and equal tension on all movements.

Unaffected by temperature.



Model B Professional \$300.00
For Bell & Howell and Mitchell Cameras and their respective Tripod. With the **ORIGINAL instant release telescopic handle.**

FRED HOEFNER

GLadstone 0243

5319 Santa Monica Boulevard
LOS ANGELES, CALIF.




Model A for Amateur motion picture cameras. Attaches to any standard STILL Tripod, \$12.00.

Trueball tripod heads are unexcelled for simplicity, accuracy and speed of operation.

The Hoefner four-inch Iris and Sunshade combination is also a superior product.



MAX FACTOR'S
NEW
Satin Smooth
LIQUID FOUNDATION
A REVELATION IN FACIAL MAKE-UP



EASTMAN
DUPLITIZED
POSITIVE FILM

EASTMAN 1359
Sound Recording
FILM

EASTMAN
SUPER X
NEGATIVE

EASTMAN
FINE GRAIN
BACKGROUND

EASTMAN
POSITIVE
FILM

EASTMAN
DUPLICATING
NEGATIVE

J. E. BRULATOUR, Inc.

New F 2.7 TAYLOR-HOBSON COOKE LENS

now standard with FILMO

70-D, 70-E, AND 121 16-MM.

Cameras

70% greater speed... ideal correction for both color and monochrome movies

The new Cooke 1-inch F2.7 lens makes movies possible under a wider range of lighting conditions. It extends the camera's use indoors and is of particular value when making Kodachrome or other color movies. This lens gives the sharp, crisp pictures which have made Taylor-Hobson lenses the choice of professional film producers throughout the world. It is, of course, instantly interchangeable with the fast F 1.5 and other Taylor-Hobson lenses.



FILMO 121

This featherweight camera, measuring only 2¼ x 3½ x 5¼ inches, loads instantly with 50-foot film magazine, permitting free interchange of black-and-white and color film, with no film spoil-

age. Offers built-in exposure calculator, two film speeds (16 and 24), single frame exposure, and typical B & H sturdy, die-cast, aluminum housing. Filmo 121, with F 2.7 lens, \$72.50. Case, \$7.50.

EXTRA TAYLOR-HOBSON LENSES FOR FILMO 16 MM. CAMERAS

Each Filmo is designed for use with a wide range of Taylor-Hobson lenses. These lenses make excellent gifts for owners of Filmo 16 mm. Cameras.

15 mm. F 2.5 universal focus, \$45.00

15 mm. F 2.5 in focusing mount, \$55.00

1" F 2.7 universal focus, \$30.00

1" F 2.7 in focusing mount \$45.00

1" F 1.8 in focusing mount, \$75.00

1" F 1.5 in focusing mount, \$75.00

2" F 3.5 in focusing mount, \$55.00

3" F 4 in focusing mount, \$72.50

4" F 4.5 in focusing mount, \$75.00


6" F 4.5 in focusing mount \$115.00

6" F 5.5 in focusing mount, \$75.00

BELL & HOWELL COMPANY

CHICAGO • NEW YORK • HOLLYWOOD • LONDON

World's largest manufacturer of precision equipment for professional motion picture studios



FILMO 70-D

This, the master of all personal movie cameras, is pictured above. Seven speeds: 8, 12, 16, 24, 32, 48 and 64 frames per second. Three-lens turret, variable spyglass viewfinder, relative exposure indicator for speeds other than normal, accurate speed governor, 216° open shutter segment. Critical focuser is optional. Hand crank, electric motor drive, and 200- or 400-foot external magazines are available as extra equipment. Filmo 70-D, with F 2.7 lens, \$188. Case, \$24.50.

FILMO 70-E

The 70-E is similar to the 70-D, lacking only its turret head and the variable area feature of the spyglass viewfinder. Operates at 8, 16, 24, and 64 frames per second. Like the 70-D it has 100-foot 16 mm. film capacity and may be fitted with the same accessories. Filmo 70-E, with F 2.7 lens, \$133. Case, \$17.

FILMO 75

The 75 is the lowest-priced 100-foot capacity 16 mm. camera of quality. Its light weight, compactness, and exquisite beauty have made it a favorite for general field or sport use. Small enough to slip into a coat pocket. Operates easily in one hand at the normal speed of 16 frames per second. Filmo 75, with F 3.5 lens, \$59.50. Case, \$5.50.



Bell & Howell Company
1848 Larchmont Ave., Chicago

Please send me booklet about ☐ Filmo 16 mm. Cameras and lenses; ☐ 16 mm. Projectors; ☐ 8 mm. Movie Equipment. Also the name of a nearby Filmo dealer.

Name _____

Address _____

City _____ State _____



AMATEUR MOVIES

25c

DECEMBER
1935

this issue

Filming Snow with Filters
Interiors Without Lights
Christmas Continuity
Elements of Composition
... and other features



IT KNOWS ITS WAY AROUND THE HOUSE!

YOUR Christmas sequence may call for a wide variety of shots—from Father trimming the Christmas tree to the children hanging up their stockings in the firelight.

And, to avoid disappointment . . . we suggest that you load your camera with Agfa 16 mm. Fine-Grain Superpan Reversible Film . . . a film that is specially designed to meet all types of indoor lighting conditions.

This film has exceptional speed and is

sensitive to all colors, including red. Its unusually wide latitude tends to minimize errors in exposure, whether you're working by daylight or by ordinary electric light.

And—its extreme fineness of grain gives you larger, more brilliant screen projection, with greater depth and detail and without noticeable grain.

Agfa 16 mm. Fine-Grain Superpan Reversible is available in 100-foot rolls at \$7.50, and in 50-foot rolls at \$4.00, including processing and return postage.

MADE BY AGFA ANSCO CORPORATION IN BINGHAMTON, N. Y.





PROFESSIONAL Criticism of the Amateur picture is a part of the service offered by the **AMERICAN CINEMATOGRAPHER**. Many are not aware of this. Hundreds of pictures have been reviewed this past year by members of the American Society of Cinematographers for the Amateur.

AMATEUR MOVIE SECTION

Contents . . .

FILMING Snow Scenes with Filters by Karl A. Barleben.....	532
INTERIORS without Lights by William Stull, A.S.C.....	533
CHRISTMAS Continuity by J. Dickinson Reed.....	534
BUILDING a Home Made Wipe-off by Arthur Wolf.....	535
DEFINITIONS of Elements in Composition by J. Belmar Hall.....	536
MAKING Fades in Positive by Thos R. Barrabee.....	537
MAKING Your Own Spotlight by J. Hammel.....	538
WHEELS of Industry.....	540

Next Month . . .

- There will be more about interior lighting. Commonsense advice with simple equipment on how to get the most out of what you have on your interior shots.
- Another interesting gadget will be presented . . . something you can make yourself.
- A timely continuity, and of course other good suggestions.
- But the biggest news will be the announcement of the 1935 Amateur Movie Prize winners.



Photo by Karl A. Barleben, Jr.

Filming Snow Scenes With Filters

ONE of the wonder-spectacles of winter is a snow storm and its results. Filmers in sections where snow is not an uncommon event have at their disposal some of the finest picture material imaginable, for while snow is white, and therefore possibly drab and uninteresting to some workers, it holds certain beauties which never fail to go over big on the home movie screen—if the filming is done correctly. Make no mistake—shooting snow is not as easy as it looks, for if the delicate textures of snow are to be preserved, you must do more than merely press the button of the camera. In an effort to outline briefly a few of the essentials in snow photography, it might be well to dwell a few moments on the fundamentals of this fascinating work.

The professional movies frequently contain snow scenes which are photographic gems—crystal clear and bright, alive with sparkling sunlight, rich in shadow and snow detail and texture. Many the amateur filmer has seen such scenes and attempted to duplicate them, only to become sadly disappointed with his efforts along these lines. Why? Principally because a few elements of snow photography were over-looked or ignored.

In order to fully understand snow photography, it is necessary to understand snow. One of the most important things to remember is that while snow appears white to the eye, in truth it reflects various colors which are nearby. This is easy to understand, but there is another tricky phase: the shadows in snow. Tracks, foot-prints, ruffles, and all other manner of indentations in snow naturally cast shadows which, to us, appear as dark or black. Actually these shadows are **blue**—notice this for yourself the

by
Karl A. Barleben, Jr.

next time snow is on the ground, for the truth of this statement. The shadows being blue, then, do not readily manifest themselves on the film, blue photographing as white, resulting in snow which lacks texture and detail—we are all familiar with the white-wash effect in which only a plain expanse of white is to be seen. It looks as much like snow as a bucket of milk! Such results are indeed discouraging, yet can be readily remedied by the use of a filter.

Just which filter to use to bring out the shadows and details depends upon several factors, chief of which is the amount of correction desired. With a panchromatic film, a pale yellow filter such as the Wratten K-1, will produce a normal reproduction of snow on the film as the eye sees it—the blue shadows will be shown as dark in the picture, and the texture of the snow brought out quite clearly and satisfactorily. A heavier filter, such as the Wratten G will produce over-correction to some extent, while a Wratten 23-A or A will result in decided over-correction. These filters may be properly classed, for this purpose, as effect filters, although there will arise circumstances where they are the means of producing very

Continued on Page 549

Interiors Without Lights

Rep - June '50 - etc

by
William Stull, A.S.C.

AS I WRITE this, a strong beam of sunlight comes through a window by my desk, lighting me warmly. Now, if I was outside the window, in the same sunlight, no one would deny that a member of the sixteen-or-eight brigade could photograph me — granting, of course, that he cared to waste film on so unprepossessing a subject. Why not inside the window, as well? The sunlight seems almost as strong and warm: what's to prevent using it for photography?

Putting the question up to my Weston meter, I find that outside the window, the correct exposure with Super-Pan would be about $f:16$ —and that inside, the sunlight areas would be correctly exposed at $f:8$. Obviously then, a passing cinefilmer could get a very nice shot of me here, without using any lights.

But it would be distinctly a one-sided lighting: the side of my face toward the window would be strongly lit, while the side away from the window would be heavily shaded.

Outdoors, the answer to such a lighting problem would be to use a reflector on the shadow-side, to throw some of the sunlight back into the dark side of the subject. Well, the same thing would work quite as well indoors as out. Placing the reflector in the proper place we could throw back enough light to brighten up those heavy shadows without flattening the picture by wiping them out completely.

And there, in a nutshell, is the secret of making interior scenes without lights: use the light from a window for the highlight side of your shot, build up the illumination in the shadows with reflectors—and there you are! It's as simple as that.

The simplest sort of lighting, of course, is the cross-light just described, and sketched in Fig. 1. Next to that (and usually more pleasing) is a straight or three-quarter front-light, as seen in Fig. 2. In this case, the window through which the light comes should be rather wide, to simplify placing the reflector. Naturally, with this sort of lighting, the direct sunlight will fall on more of the background area, giving you more depth in your shot. Where the sun does not strike, your picture will be either a jet-black shadow, or badly underexposed, unless you have additional reflectors to throw light on the background as well as on the subject.




Fig. 1.




Fig. 2.




Fig. 3.

Sometimes, too, you can make very effective back-lit effects this way, placing subject and camera as shown in Fig. 3. Two reflectors will be necessary, one on each side of the camera, with one nearer the subject than the other, so that we still have a highlight side and a shadow side. For the best results, the sunlight should come from a rather high angle, and it is well if some shrubbery or the like is outside the window, blocking off the lower half through which we would otherwise shoot—and thereby eliminating the uneven exposure between the foreground and that part of the background seen through the window.

These effects, though, are among the more elementary ones we can get indoors. If we have really fast lenses—say, $f:2.5$ or faster—we can get away from the direct sunlight and its harsh lightings. There is really a surprising amount of light to be found by windows through which the direct rays do not come—and it is a softer, diffused light which gives infinitely more satisfying photographic rendi-

Continued on Page 542



Continuity for a Christmas Comedy

by
J. Dickinson Reed

MAIN TITLE: DEAR SANTA.

Scene 1. LONG-SHOT of a group of boys playing in the snow.

Scene 2. MEDIUM-SHOT of same. One of the boys, "Buddy," is seen to stop, pull out his watch, and start to leave. The others cluster round him, urging him to stay a little longer.

Scene 3. CLOSE-UP of "Buddy." He indicates plainly that he has to go, and moves forward into the camera. FADE OUT.

Scene 4. FADE IN. Long-shot inside of house, in front hallway. Buddy comes in, hangs up his coat and cap, and hurries up the stairs.

Scene 5. CLOSE-UP of bathtub faucet as water is turned on.

Scene 6. CLOSE SHOT of floor in corner of bedroom.

Buddy's garments are thrown into the scene, one after the other.

Scene 7. CLOSE-UP of Buddy's bare feet hurrying down hall.

Scene 8. CLOSE-UP of feet entering bathroom.

Scene 9. Medium CLOSE-UP of Buddy in bathtub, very energetically soaping himself.

Scene 10. CLOSE-UP of Buddy in tub, actually washing behind his ears.

Scene 11. LONG-SHOT of Buddy, enveloped in a big bath-towel, drying himself.

Scene 12. MEDIUM-SHOT of Buddy, in his BVD's, getting out a clean shirt.

Scene 13. CLOSE SHOT of Buddy, fully dressed in clean clothes, in front of the mirror, combing his hair. He is taking great pains with it—when he finishes, he surveys himself critically, picks up the comb again and smooths out one slightly out-of-place lock, sets the comb down, and turns as if to go.

Scene 14. LONG-SHOT in the dining-room. The table is set for lunch. Mother comes in with the last dish, and goes to the door, as though to call Buddy.

Scene 15. Medium LONG-SHOT toward door. Mother enters the picture, and just as she reaches for the doorknob, the door swings open, revealing Buddy, washed and combed and dressed in his best. Both stop.

Scene 16. CLOSE-UP of Mother. She is speechless with surprise.

Scene 17. LONG-SHOT toward door, with table in foreground. Buddy marches past Mother, and takes his place at the table. She follows him, and starts to serve lunch.

Scene 18. CLOSE-UP of Buddy, eating. Shoot this at 8 frame-speed to show him eating at racing speed. LAP-DISSOLVE (or fade out and in) TO

Scene 19. CLOSE MEDIUM-SHOT of Buddy (normal speed). He has finished eating. He pushes away his empty plate, folds his napkin, and leaves the table.

Scene 20. LONG-SHOT in dining-room. Buddy comes in, wearing his overcoat and rubbers, and carrying his cap. He kisses Mother good-bye, and leaves.

Scene 21. LONG-SHOT of Buddy walking briskly down the street.

Scene 22. LONG-SHOT at corner. Buddy gets into a street-car.

Scene 23. CLOSE-UP of Buddy in street-car, made from within the car. He sits expectantly, glancing out of the window now and then.

Scene 24. LONG-SHOT at down-town street corner. A street-car stops, and Buddy gets out.

Scene 25. LONG-SHOT on down-town street. Buddy is seen walking hurriedly along, weaving around the slower-moving shoppers.


Scene 26. LONG-SHOT of entrance to big office-building. Buddy enters the scene and goes into the building. LAP-DISSOLVE (or fade out and in) TO

Scene 27. Same as Scene 26. Buddy and Father come out of the building together, and walk off.

Scene 28. Medium LONG-SHOT of crowd gathered before a store-window.

Scene 29. Series of CLOSE-UPS of children with their noses pressed close against the glass.

Continued on Page 543



Building a Home Made Wipe-off

THIS simply built combination sun-shade and wipe is made of material easily shaped and cut and available to anyone.

Tin is used for the foundation; the finish is black cardboard glued to each side the tin after it has been cut into the desired sizes and shapes.

The wipe wings are made to operate smoothly as shown in Fig. 2 by operating them in unison by means of the small gears shown at the center bottom of the box and on the inside lower corners of the wipe blades.

Usually illustrations can tell more quickly and plainly how a thing operates and is built. Therefore if you will refer to Fig. 1 you will see the box as it looks from a front view with the wipe blades closed. The next figure shows the blades slightly open giving a fan effect to the picture. The next figure which is Fig. 3 is a rear view of

by
Arthur Wolff

the effect box. On this sketch you will see a small block of wood at the bottom used to fasten the center gears.

Fig. 5 is the assembly less the wipe wings. Fig. 5 together with Fig. 6 gives you the complete assembly. Fig. 6 is merely a ruler bought in the 5-and-10-cent store. The hole drilled in the right side is for placing over the screw in the tripod so as to fasten this ruler between your camera and the tripod head. The other end of the ruler goes through the slot at the bottom of Fig. 5. The entire outfit assembled is shown in Fig. 7.

Fig. 4 is the complete sunshade and effect box. This fits in the upper opening of Fig. 5 which is a frame work made to hold this and the ruler.

Fig. 5 calls for a more rigid material as this portion of the assembly must carry whatever weight the device might have. I made Fig. 5 out of wood.


While this is built merely for a fan wipe, the imaginative constructor will possibly find many other ways of applying wipe blades. The material used is so cheap and plentiful that if a device of this sort is used only a few times it pays for itself.

Most of the gadgets I build for my camera are made from tin. This works very easily and as a general rule the tools I require are merely a knife and scissors.

After my patterns are cut I put them in their proper place and hold them together with black gummed paper tape (the same as is used for lantern slides).

I have not given measurements as they will be governed by the type of camera you are using. However, as a guide I might mention that the outside dimensions of the box as shown in Figs. 1, 2 and 3 are 3"x3"x1 1/4". The measurements of Fig. 4 are 3" high at front, 3 1/4" from front to rear, and the rear is 2" square. The hole, of course, is governed by lens size. The height of Fig. 5 is 5 7/8", the width 3 3/8".

Those who like to make their own gadgets will find this simple to construct.





Definitions of Elements in Composition

LINE: Design begins with line. Connected and inter-laced lines create areas. In architectural and costume design, lines denote qualities that are important; i.e.

VERTICAL
HORIZONTAL
OBLIQUE
SPIRAL or CURVED LINE
BROKEN

Structural lines are found in the fireplace, furniture, in the doorway and windows; in the silhouette of a costume.

A line may be narrow or wide. The wider it is, the more it is like an area. A line or lines within the outline add interest and complexity to a subject, such as architectural relief, embroidery pattern, wall panels, etc.

It will be found that a tone of dark is formed by the association of two or more lines, this tone may be darkened by increasing the width of the lines, or by bringing them closer together.

PRINCIPLES: Variety and interest is well selected lines used together. Measured, size and number of lines of different types determine the final result.

Variety in grouping of lines eliminates monotony. The wider the line, the greater will be its accenting value.

Design must have a main axis. This starts the eye moving, other lines in the design must be subordinated to the main line. Subordination is brought about by the selection in size, length and width. The position and direction of a line is important in relation to other lines.

In a group of lines, one line or pair of lines must predominate in size and position. If a line, space or color asserts itself to the detriment of

by
J. Belmar Hall,
Instructor, Department of Cinema, U.S.C.


others the result will be discord, not harmony. The main or structural lines of an object or design determine the location of the center interest. Structural lines should determine the character and general direction of the other lines. In speaking of "good design," we mean that the line qualities and line divisions are structurally good and artistically handled.

Next month we will take up the other principles in structural design in composition. Dynamic symmetry also will be covered as this is one of the most important things in good composition.

THE AUTHOR'S GHOST

SYNOPSIS: A study in lines, angles and tricks of the 16mm camera built around a dummy figure of an author who has only saw-dust for brains. In his mad search for ideas, such that could come only from a brain of this kind, we are led a merry chase into all the abstract forms that will make a perfect montage or mounting of shots that are related to the story through the movement they express. Each shot must build up the tempo until the brain-pictures that flash through the dummy head of the author cannot stand the strain any longer as ideas meet and clash

Continued on Page 550



Making Fades on Positive

by

Thomas R. Barrabee

Chemist, Dye Research Laboratories

FILM editing, that phase of motion picture production during which the many scenes of a picture are assembled and united into a smoothly flowing story, is a very important job in the preparation of a successful picture. In this work, the film editor calls to his assistance many mechanical devices to produce the proper continuity and tempo, one of the simplest of these being the fade.

The first all metal cameras manufactured about 1912 by the Bell and Howell Company incorporated in their construction a variable gear-driven shutter mechanism by which the operator was able to continuously and evenly decrease his exposure from normal to zero over a film length of eleven feet. These cameras, which were used by Essanay, were improved shortly after to produce an eight-foot fade and finally to make a four-foot one, the length which is produced by the present camera.

When such a negative was printed, the general density of the print increased to such a point that the screen gradually became completely dark, hence the name "fade-out" which was adopted for this effect. By reversing the procedure on the beginning of a scene a "fade-in" is produced.

With the gradual development of motion picture technique, and particularly with the advent of motor-driven cameras which accompanied the introduction of the sound picture, the practice of making fades in the camera on the original negative was discontinued. A fade in a release print is now produced either by chemically bleaching the negative or by making a duplicate in an optical printer, in which case the variable shutter is again brought into play.

In the initial assembly of the picture by the film editor it is sometimes desired to see the effect of inserting a fade at some point. In this case the print is dyed. By so doing, no alteration is necessary in the original negative until such time as a definite decision is made that the fade gives the desired effect.

Such a fade made on a print with dye should be quite neutral in color, should take into the emulsion without difficulty and be quite opaque at the end. Many dyes have been tried for this purpose but up to the present time no single dye has been found with these properties. Recently a material was introduced for this known as Foto Fade which consists of a mixture of dyes and chemicals balanced to give the desired effects. Extensive tests by a number of the laboratories in Hollywood have shown that Foto Fade produces a uniform neutral fade quite simply by a mechanical dipping process.

In the majority of productions by the amateur reversal film is used so that the editing is done on a positive. Since few amateur cameras are equipped with a variable shutter mechanism, the availability of an easy and rapid method of making fades brings to hand an additional and useful tool.

A pint of water in which five grams of Foto Fade have been thoroughly dissolved is placed in a deep narrow vessel such as a cylindrical graduate. The film to be dyed is

immersed frame by frame, the lower end being weighted with a clip. The film is withdrawn in a similar manner, squeezed between damp cotton, rinsed and dried. An immersion of about one minute is necessary to render the film entirely opaque. The solution of Foto Fade keeps indefinitely and hundreds of fades can be made from a single pint of solution. Since the dye sets into the emulsion, it is not affected by projection and the result is quite permanent.

The skillful and judicious use of fades following main titles, to indicate lapses in time, changes in location, etc., adds much to the "production value" of a motion picture.


It is claimed that several of the Hollywood laboratories devoted to 35mm film have adopted this new chemical for the making of after fades. It will possibly find favor with amateurs who are not always certain that they want to make fades when they are shooting their picture, but are desirous of inserting them after the picture is made. This is the method used today by the professional laboratories in Hollywood. The fades, while not made chemically are made in the printer which of course is possible with negative and positive. The first prints turned out for the cutter do not have these effects, they are determined after the picture is cut.

It is well to always stir a chemical such as this fade before using, it is only natural that some of the heavier elements will be inclined to drop to the bottom of the container and, of course, your film would not receive the full effect of the dipping.

You can tell when your chemical is not properly mixed. Your print will show a strong reddish cast.

It is well not to make fades too long. Remember you must make a fade in and a fade out to make the scene smooth, so a foot fade out and a foot fade in is in most instances plenty. This means five seconds on the screen before the complete fade in and fade out is completed.





A and B, end and sectional views of partly-finished wooden spotlight. C, snout; D, concentrator for desk-lamp.

Making Your Own Spotlight

by
J. Hommel

HOME-MOVIE interior scenes frequently call for spotlight effects. The equipment people have been very nice indeed about making inexpensive general lighting units for home filming, but so far they've been less considerate in the matter of turning out spotlights. Only one home-movie spotlight has appeared on the market so far: and aside from this, the cinefilmer's only alternative is to buy a professional "baby spot," and these—unless one is lucky enough to pick up a used one at a theatre-supply shop—come rather higher than the average amateur cares to pay.

But it is quite possible to build your own spotlight, or even to improvise crude makeshifts that will to a certain extent, give spotlight effects.

The simplest sort of a makeshift is made by putting a Photoflood into an ordinary reading-lamp, and fitting a tubular hood over the lamp's reflector. If the tube is long enough, it will cut off the spreading rays at the edge of the beam, and give a round spot of light which is good enough for some purposes. The simplest thing to use for this tube is a length of ordinary stove-pipe. Take a short strip of pipe, slit one end of it with shears, and fold them down so that they fit over the lamp's reflector. Then slip a longer piece of the stove-pipe over this—and there you are! If you want to be really ritzy, you can fit a third section of pipe (just a shade larger) over the tube, so that by moving it in or out you can to some extent control the size of the spot.

Another gadget is the "snout" or concentrator, which has several times been described in this magazine. It is used over any ordinary photographic light, and gives fair spot effects. Go to any shop where they make sheet-metal spinings, and have a cone made; the big end should be approximately the same diameter as the front of the reflector of your regular lamp. The small end should be about six inches across. Then rivet three little spring clips at intervals around the big end, and you'll have a "snout" that fits your floodlight.

These makeshifts will work well enough, but they waste a lot of light. You see, in a real spotlight, to make the beam smaller, you move your globe closer to the focus of the lens, rather than simply cutting off the edge of the beam: so you get a stronger, concentrated light as you pull the beam down. With either the snout or the stove-pipe gadget, you simply cut off the edge of the beam and, so to speak, throw the light away. Whether you cast a big spot, or a tiny one, the intensity of light is the same. Pointing a photocell meter at such a lamp, your reading would be the same whether you had a large spot or a small one; but with a true spotlight, you'd get a low reading—say around 200—when the beam was flooded out, and kick the needle clear off the dial when the beam was spotted down.

It is fairly easy to build a real spotlight, too. The heart of the lamp is a plano-convex condensing lens, which can be bought at any photo-supply store for a few dollars. The larger the diameter of the lens, the more light you'll collect from your light-globe, incidentally; but its focal length will probably be longer, too, so your lamp will have to be bigger.

If you are a fair carpenter, wooden construction will do. Build your box out of three-fourth inch plywood, and make it large enough to allow reasonably ample air-space around the globe, and long enough so that the globe will be in focus at the rear end of its travel. The globe itself can be mounted in an ordinary ten-cent-store socket (porcelain will probably stand the heat better than Bakelite). This socket should be screwed to a square block of wood thick enough so that the center of the lamp-globe will be even with the center of the lens. The block should project a little on each side of the socket-base. Two strips of L-shaped molding are mounted upside-down along the bottom of the box, and serve as guides for the lamp; the projecting edges of the base-block fit under these rails.

There are two ways of controlling the focus of the lamp. The simplest is to cut a small slit in the bottom, between the rails and running the length of the lamp; a bolt passes through this from a hole in the wooden lamp-

Continued on Page 544



Christmas for keeps
when you give Ciné-Kodak

NO one knows better than you how thrilling home movies really are. So what better present could you make to those you want to please the most than Ciné-Kodak Eight?

Think of the fun they'll have in seeing their own movies clear and brilliant on the screen. Christmas for keeps—that's what they get when some one gives Ciné-Kodak Eight. Christmas and a thousand-and-one other lovely, memorable days they'll want to save.

It's a movie camera of remarkable economy, giving four times as many

movies per foot of film. A roll of "Eight" film runs as long on the screen as 100 feet of any amateur standard home movie film. 20 to 30 movie scenes—each as long as the average scene in the news reels—on a roll of film costing \$2.25, *finished, ready to show*. This means movies at ten cents a shot. The "Eight" costs only \$34.50. See it, and samples of the movies it makes, at your dealer's.

What to give that's new, fresh, and will win everybody's heart? The "Eight" settles it. Eastman Kodak Company, Rochester, N. Y.

Eight



GIVE A KODAK

...ready for the holidays in its own Christmas wrapping.



WHEELS OF INDUSTRY

Reflex Box Camera

● Burleigh Brooks announces the K. W. Reflex Box Camera which takes $2\frac{1}{4}$ by $3\frac{1}{4}$ inch roll film and has self-erecting hood of the usual reflex type, containing focusing screen or ground glass, which shows an image of the subject in exact size and in sharp focus.

The all-metal slit shutter is adjustable for speeds of $1/25$, $1/50$ and $1/100$ second and for brief and long time exposures. The scales for stops, distances and shutter speeds, are conveniently arranged to insure instantaneous manipulation. Its dimensions are $4\frac{7}{8}$ by $3\frac{1}{8}$ by $4\frac{1}{4}$ inches, and it weighs approximately two pounds.

Weston Film Chart


● Weston Electrical Instrument Corporation has issued an interesting and valuable chart for both the still and cine photographer. It is called Weston Film Speeds and can be secured from practically every dealer for the asking.

This chart gives the Weston reading for meters Nos. 617, 627 and 650 of all popular types of film. It gives a very clear and comprehensive outline on the use of Kodachrome.

One other chart of great value to the cine amateur is the "Shutter Time for Motion Picture Cameras." This exposure time is given based on 16 pictures per second.

New 8mm Camera

● Hans Unfried of Buffalo, N.Y., announces that he is importing the German-made Cine Nizo 8mm camera for marketing in the United States.



This camera is furnished with a 12.5mm focal length lens with a speed rating of $f/2.8$. It will run 15 feet of film with one winding. It is adjustable for speeds from 8 to 64 frames per second. In Germany lenses of 20mm, 35mm and 75mm focal lengths are available. It has what is termed a three-in-one finder which serves as direct, indirect and angle viewfinder.

Cine Humidor

● Wm. J. Grace, of Dallas, Texas, announces an addition to his line of useful cine accessories. His latest contribution is the Strongbox Humidor. It is a simple box without the regular catches and locks and hinges. It is built very substantial and comes in two sizes: one for 6 reels of 200 feet 8mm and one for 6 reels of 400 feet 16mm. All six reels are stacked over a center rod, the top of which is threaded to receive the castel nut which holds the top firmly on the case. A piece of $3/16$ by $1\frac{1}{2}$ inch felt in one corner is moistened to keep the films properly humidified.

Camera Accessory

● The photography of wild life usually calls for extreme caution and care on the part of the cameraman. In most cases, it is impossible for him to approach birds and animals sufficiently to secure a reasonably large image on his film. A device which permits camera control from a distance has long been recognized as a definite aid to the nature photographer. E. Leitz, Inc., announces a special remote control device for the Leica camera.

The Leica remote control device consists essentially of a pulley arrangement by means of which two cords release the shutter, and rewind the film and shutter for the next exposure. The length of the cords can be increased to any length required, and permit the cameraman complete and easy control over the action of the camera mechanism.

Tank Agitator

● E. LEITZ, INC., announce a new, domestic agitator. The movement imparted to the developing tank is an oscillating one instead of the usual constant, one-direction movement. The developing tank is merely placed upon the circular platform or table and the switch turned on. A husky motor propels the platform to and fro.

Two models of the Leitz agitator are

available, one for A.C. (alternating current), the other for D. C. (direct current). The two models are identical other than the current for which they are intended.

An accessory to be used in connection with the agitators is an automatic time-switch which permits time intervals of up to 30 minutes to be obtained without any attention from the owner. At the end of the predetermined time interval, the switch shuts off the current automatically.

Special Leica Models

● The Leica camera with its 30 to 36 exposures per loading may not entirely suit some photographers. Some want to make but one exposure at a loading, while others have need to make 100 or more at a loading. In order to accommodate these extremes, E. Leitz, Inc., 60 East 10th St., New York City, supplied the "Oligo" Single Exposure Leica and the Model FF Leica.


The Oligo Model uses tiny metal "plate holders," which will accommodate sections of 35mm film. A ground glass focusing screen and special Isbors shutter are supplied. All standard Leica lenses may be used with this model.

In the Model FF, the owner has sufficient film capacity to make 250 exposures without reloading the camera. Basically the Model FF is the same as the Model F, excepting for the enlarged ends which accommodate film magazines holding up to 30 feet of film. Aerial, natural color, copy and record photographers often have a need for such a camera.



De Vry Sound Camera

● There is always interest among photographers in a new camera. The DeVry

Continued on Page 547



Give for a Lifetime!



Gifts

such as these are more than mere tokens of remembrance. They reflect magnificently the gracious and wholehearted generosity of the giver . . . and, being VICTORS, they bear the distinction of being the "Finest that money can buy."

VICTOR CAMERAS are available in three Models . . . MODEL 3 (illustrated here) is only \$72.50 with F 2.9 one inch fixed focus lens; MODEL 4 with VISUAL FOCUSING, 3-lens TURRET FRONT, etc., is priced at only \$137.50, with F 2.9 one inch focusing mount lens; MODEL 5 with all features of Model 4, PLUS REVERSE ACTION lists at \$200.00 with F 1.5 one inch speed lens.

VICTOR SILENT PROJECTORS embody many outstanding refinements such as PATENTED Automatic Film Trip which protects priceless films from costly damage! Priced at \$120.00, \$135.50, and \$185.00. MODEL 21 with beautiful walnut cabinet and antique silver fittings is especially appropriate for Christmas giving.

VICTOR SOUND-ON-FILM ANIMATOPHONES are the world's most widely-used 16mm sound equipments. Finer performance and many exclusive features have made them such! Priced at \$360.00, \$540.00, and \$565.00. MODEL 25 (\$360.00) makes a particularly splendid gift for the home.

Write for illustrated literature and name of nearest dealer.

VICTOR ANIMATOGRAPH CORP

DAVENPORT, IOWA

NEW YORK CITY

CHICAGO

LOS ANGELES

**16
MM**

REG. U.S.
PAT. OFF.

Victor

16mm SOUND-ON-FILM

Latest Releases

Rent Exchange Sale
Write for descriptive catalogue.**H. B. KAY**

40 Linden St. Brooklyn, N.Y.

**Give at Christmas!
Britelite Truvision****PRODUCTS
of CHARACTER
SCREENS**

"For Perfection in Projection." Made in all popular models for every purse and purpose.

Deluxe A, Crystal Beaded Screen, 30x40 - \$15



TRIPLE XXX and BIG BEN MODEL REFLECTORS are efficient lighting units for Movie and Still Photography.

Big Ben - \$1.50
Triple XXX - \$8.75



FILM STORAGE AND PROJECTOR CASES . . . constructed in a manner fitting to the finest cabinet and luggage manufacture.

**At all Dealers
Literature on Request**

Motion Picture Screen & Accessories Co.
520 West 26th Street New York

**PROTECT THEM**

Today one of the duties of parental love is to protect children from their arch foe, tuberculosis—the greatest cause of death between the ages of fifteen and forty-five. Christmas Seals help you protect your children from this disease.

**BUY
CHRISTMAS
SEALS**

The National, State and Local
Tuberculosis Associations
of the United States

Interiors Without Lights

Continued from Page 533

tions. This softer light can usually be reflected very satisfactorily, too, while if necessary, a beam of direct sunlight from another window can be bent around with reflectors, until it is useful. Once one gets the hang of using reflectors, it becomes quite possible to juggle a beam of light from one reflector to another until it is where we need it.

These reflector lightings can be made very successfully on porches, too. A light-colored porch floor is in itself something of a reflector, by the way. Shooting into a porch presents little difficulty; but shooting through, or out from a porch one should remember that the direct and reflected front-light on the subject should be rather strong, so as to minimize the difference in exposure between the subject on the shaded porch and the more brilliantly illuminated background.

And how are reflectors made? Well, the simplest reflector is simply a piece of white cloth, like a sheet, held up in the proper place to throw back some light into the shadowed side of the subject. A very simple support for such a reflector can be made by taking two strips of light wood, and fastening them together to form a T. In use, you simply fasten the sheet onto the cross-bar of the T with pins or thumb-tacks, and then attach the upright of the T to the back of a chair with a strong rubber band. As you usually want your reflector at an angle, you can put a weight on the bottom of the sheet, and adjust the angle by moving the chair to and fro, and by sliding the supporting bar higher or lower on the back of the chair. This type of reflector is useful mainly when the direct light is quite strong, for it reflects quite diffusely. Projection-screens can also be pressed into service as "soft" reflectors.

But more often, a surface that has greater reflecting power will be needed, and it is best to use a reflector more like those used professionally. This type consists of a piece of composition board or plywood coated with tinfoil. You can make them almost any size that is convenient; it is a good idea to make them in two sections, hinged together like a book, so that when not in use, the reflector can be folded into smaller compass, protecting the reflecting surfaces. A hinged wooden leg at the back will support the reflector at any desired angle. If the reflectors are going to be used indoors a second leg can be hinged at the bottom, and fitted with notches into which the upper leg can fit, thereby avoiding the trouble encountered on slippery floors.

Where you want a very "hard" reflected light, you can use a sheet of tin or a mirror: but the beam from such a reflecting surface is so intense that it is not very pleasing photographically, and hard to control.

On the other hand, when you want to soften the direct light through a window, it can often be done by covering all or part of the window with thin cheese-cloth.

The color of the room in which you are working will have a very important bearing on the sort of picture you will get. If the walls and hangings are dark, they will naturally reflect very little light into the lens—not enough to make any impression upon the film—and about all you will get is whatever is in the path of the direct light through the window, or in the beams of the reflectors. On the other hand, if the walls are light in color, they will reflect more light into your lens, and consequently show up better in the picture.

Following the same idea to its logical conclusion, we can make a very few lights go a long way if we supplement them with daylight—and still farther if we also use reflectors. For instance, using sunlight and a reflector to light our subject, we would probably lose most of the background: but if we use a single lamp, we can add enough general illumination to reveal the background fairly well, too. Used this way, in conjunction with the natural illumination of a room, one lamp—a single, inexpensive Photoflood unit or even a reading-lamp with a Photoflood globe—will enable us to film a surprising range of indoor scenes. As the strength of the illumination varies as the inverse square of the distance between the lamp and what it illumines, we can balance our natural and artificial lighting simply by moving the lamp in or out from the subject. I have made many excellent interiors this way, using a single lamp and sunlight even at times when I had several lamps available; the effect on the screen was more completely natural than if I had tried to avoid the sunlight and use artificial lighting entirely. Some of my finest Kodachrome interiors, too, were made by taking advantage of a beam of sunlight in a light-walled room, and merely filling in with a single electric light.

Many amateurs are inclined to overlook the fact that if they can reflect sunlight, they can also reflect the rays of a photographic lamp. Used intelligently, good reflectors can make a single lamp virtually equivalent to two un-

New! The Da-Lite Number 2 UNIPOD

... the very latest thing in a compact, light-weight camera support. Developed for those who want the convenience of the No. 1 UNIPOD (see below) in a shorter model. The No. 2 rests against the body and is supported by a strap around the neck. It is made of two aluminum tubes, that telescope. When




collapsed, it is only 11" long. It extends to 17½". A half turn of the knob on the upper end of the inner tube locks the two members securely at any height. A threaded extension on this inner member receives the camera and holds it firmly. The No. 2 UNIPOD is a *different* Christmas gift that any movie maker will be delighted to receive. See it at your dealer's today or write for full details!

SOMETHING DIFFERENT

In Christmas Gifts for Your Movie-Maker Friends!

DA-LITE MOVIE ACCESSORIES




The DA-LITE Projector Stand

makes home movie shows run as smoothly as professional presentations. It permits placing the audience in the best location . . . directly in front of the screen and elevating the projector above their heads. It is equipped with either a tilting silent projector platform (with side clamps to grip the projector) or a non-tilting table for sound and slide projectors. Sturdy and vibrationless. Your dealer will gladly demonstrate.



DA-LITE No. 1 UNIPOD

Keeps the camera steady, prevents wobbly pictures. Extends to any height up to 60"; collapses to snappy appearing walking cane. Sold by leading dealers everywhere. Or write us for full details and name of nearest distributor!



DA-LITE Portable Screens

For the friend who is trying to get along with a makeshift screen, there is no more welcome gift than a Da-Lite Beaded Screen. Movies are sparkling clear, and have greater depth and brilliance. There are models for every need. Illustrated is the famous Challenger which has its own tripod and can be set up anywhere. Ask to see the Da-Lite line now, before the last-minute Christmas rush. Prices range from \$3.00 up.

DA-LITE SCREEN CO., Inc.


2723 NO. CRAWFORD AVENUE

CHICAGO, ILLINOIS

LEICA or Contax plus a good negative plus good **DEVELOPING** makes a good picture. We use Super-Soup for developing.


Morgan Camera Shop

6305 Sunset Blvd., Hollywood, Calif.



CRAIG JR. SPLICER \$3.75

Now available for use with both 8 mm. and 16 mm films.



CRAIG SPLICER \$10

Now available in 16 mm size for use with either silent or sound on film films

CRAIG MOVIE SUPPLY Co.

1053 So. Olive

Los Angeles, California

Represented by Ampro in the East

its, two equal to four, and so on. Anyone whose lighting equipment is limited should certainly try using reflectors.

Finally, by investing a few extra dimes in extension-cords, it is possible to carry your lights outdoors, and to use them for what the professional terms "booster" lighting. In other words, when shooting on shady porches, or in other shaded places near a house, you can use your lights like reflectors—to fill in what would otherwise be heavy shadows.

A while ago, for instance, I was making some 16mm films in a friend's house. There was a chance for a beautiful shot of a man and a girl on a big porch; seating them toward the edge of the porch, I could get a beautiful back-light from the rays of the afternoon sun. But the exposure-problem was perplexing: if I opened up enough

to get a good exposure on the shadowed faces, the brilliantly lit background would be burned up, while if I exposed for the background, I'd lose the more important faces. A reflector would solve the problem nicely—but I had no reflector. So I strung up my lamp-cords together, and brought a 500-Watt Kodalite out onto the porch. Placed beside the camera, it gave me a nice, even lighting on the faces (in this case, a flat front-light would be the most natural effect), and allowed me to balance the exposure between the faces, the strong back-light, and the brilliant background. On the screen, the effect is remarkably natural, without any hint of artificial lighting. And every cinemateur who sees the film asks, "How did you get that shot without burning up the highlights?" The answer is simply—"Filling in the shadows!"

Making Your Own Spotlight

Continued from Page 538

base, and is fitted with a wing-nut and washer by which the lamp can be locked at any position. This is easy to make, but unfortunately, the wing-nut often gets quite warm when the lamp is burned for any length of time, which makes things a bit inconvenient. The other method is to fit a wooden shaft—a strip of doweling will do excellently—to the lamp-base, carrying it out through the back of the lamp. This way, you can slide your lamp in and out of focus, flooding it or spotting it, without risking burned fingers.

The back of the lamphouse should be hinged, to facilitate changing lamps.

It is a good idea to drill several holes along the lower edge of each of the two sides, to allow for ventilation, and to hinge a narrow cover at the top, which can be opened slightly when the lamp is burning, again for ventilation. Too much heat materially shortens the life of a Photoflood. If your handiwork is particularly good, you can make this top ventilator a long, narrow box-like affair, fixed in place, and with ventilating holes in its sides.

The lens, of course, is mounted in front of the lamphouse. The simplest way to do this is to cut a hole slightly smaller than the diameter of the lens in the frontboard, then to ream out the hole to lens-diameter and about three-eighth inch depth. The lens is fitted into this, with the flat side toward the lamp (that is, inward), and held in place either by a loop of heavy spring-wire, by the little metal fasteners used to hold window-glass, or by putting with plastic wood. Of course, if you're an amateur woodworker and have a lathe, you can turn out a flanged hardwood lens-mount de luxe, which can be fitted in place with screws.


To support the spotlight, you will need a stand which can be raised or lowered, and a mounting which will let you "pan" and tilt the lamp to any angle. A cheap music-stand will do excellently for the stand, while the lamp-bracket can easily be made out of a U-shaped metal strip. Have a threaded hole cut in the bottom of the U, fitting into the top section of the stand, which is also threaded. The tilting movement comes

New! A Strongbox Humidor

Two Sizes;

8mm., \$2.65

16mm., \$2.85



• Films are precious—save them from light and air damage!

• Self-humidifier built in. Requires no individual film cans.

• Sturdy construction—heavy gauge metal—no flimsy hinges or locks.

• Beautiful finish—of brown crackle—handle nickel-plated.

• Holds 6 reels—one size for 200 ft. 8mm one for 400 ft. 16mm.

Wm. J. Grace
SPECIALLY DESIGNED CINE

312 WEST PAGE
EQUIPMENT AND APPARATUS
DALLAS TEXAS

A Gift


*... more desired
than ever before*



With its increased sensitivity and wider range of usefulness, the new WESTON makes an ideal Christmas gift for the picture taker. On sale at all leading dealers in an attractive gift box. . . . Weston Electrical Instrument Corporation, 598 Frelinghuysen Avenue, Newark, New Jersey.

WESTON *Exposure Meters*

for DISCRIMINATING WORKERS



KINO-PLASMAT

Superb color correction—extremely high speed — and the ability to create an image with a practically equivalent sharpness, at all planes, are the features which distinguish the Kino-Plasmat f 1.5, 1" lens from other objectives...

WIDE ANGLE LENSES

Poor light and cramped, crowded quarters present no problems that Hugo Meyer Kino-Plasmat and Trioplan 15mm Angle Lenses cannot solve. Outdoors—their 60% greater covering power adapts them ideally for architectural and landscape work.

TELEPHOTO LENSES

For Sport — the distant, elusive view and close-ups generally, Hugo Meyer Tele-Megor and Trioplan Telephoto Lenses are unexcelled. Their powerful magnification and needle-sharp definition capture the least discernible detail of objects that are practically imperceptible to the naked eye.

Catalog on Request

Hugo Meyer & Co.
245 West 55th Street New York

naturally from mounting the lamp between the arms of the U, and holding it in place with bolts and wing-nuts.

If you are not such a good carpenter, this same general construction can be carried out in metal, either by yourself or by the neighborhood tinsmith. The lamp-rails, lamp-supporting block, and so on can easily be made up of simple angle sections. Don't however, make the mistake of using too light a weight of metal for your lamp-house: it will be subjected not only to quite a bit of heat, but to a lot of unpremeditated hard knocks, so if you want your lamp to last, use a substantial grade of tinner's galvanized iron. The simplest construction for the lens-carrying front-board of your spotlight would naturally be a casting, which could be held in place with screws; but this is likely to run into more expense than necessary. A less costly construction consists of two metal plates, each with a round hole a shade smaller than the lens. The lens is mounted between these two plates, which can be spaced apart with a layer or two of the asbestos sheeting used for insulating furnaces and bolted together. The rear plate can be soldered or welded to the lamp-box, while the front plate is held only by the bolts.

It is rather important when using metal construction to have wooden handles on the operating controls, for the direct metal-to-metal contact transmits heat all too freely.

The inside of your spotlight can be painted with flat white or aluminum paint, though this probably does not greatly increase the power of the lamp; most of the light will be collected from the front side of the globe only. If you plan to use clear, projection-type globes, there is, however, a definite advantage in fitting a small, spherical mirror (likewise from a photo or theatre-supply store) behind the globe, to reflect the rearward rays back to where they can be picked up by the lens. A coat of black paint (or, in a wooden lamp, stain) on the outside of the spotlight always makes for better appearance.

By using different kinds of lamp-globes, you can get different effects with your spotlight. If you use a 500-watt projection-type globe, you will get a "harder," more intense light, with more clear-cut spot-effects, though when spotted down you will also get an image of the filament wires. If you use a regular Photoflood, you will get a much softer effect, with a not quite so definite spot; when spotted down a bit beyond the point of focus, this type of light is very effective for giving sparkle to the eyes in a close-up. Lastly, if you use one of the opal-glass type Photofloods, you will get still softer effects.

CINE KODAK SPECIAL and VICTOR FIVE OWNERS!

Give Your Camera a Real
CHRISTMAS PRESENT
DU MORR RADIAL WIPE

\$32.50, postpaid
Special Fans—\$2.50 each

J. D. COCHRANE, Jr.
734 Brooks Ave., Wyoming, Cinn., O.

The New 16mm PANCHROMATIC NEGATIVES (Eastman, Agfa, Dupont)

will surprise you with their fine quality, their beautiful tones and grainless reproductions, if you have them developed by the

**DUNNING GRAINLESS METHOD
DUNNING PROCESS COMPANY**
932 N. La Brea Avenue
Hollywood, Calif.
(35mm reduced to 16mm)


16mm RECORDING 16mm

Professional Sound Direct on Film
USING THE DOUBLE SYSTEM

Many Times Cheaper and Better Than
35mm Reductions

• Mfg. of 16mm and 35mm Recording
Heads, Amplifiers, Developing Machines,
Printers, Etc.

CINEMA ARTS—CRAFTS
918 N. Fairfax HE-1984 Hollywood, Calif.



Sound
Projector **\$195.00**
Only

Write for Detailed Plan.
Demonstrations Without Obligation.
S. O. S. CORP. 1600 Bway., N.Y.C.

TO qualified groups and organizations with limited funds we offer the advantage of a complete

**Cinaphone
16mm Educator**

sound-on-film outfit in easily-paid-for units.

A NEW ADDITION
TO

FOTOSHOP Cine Film

—8—

ULTRA RAPID

**Panchromatic 16mm
Film**

\$4.25, 100 Feet

We guarantee this film as fast under all conditions and as fine-grained as any supersensitive 16mm film now being sold.

OTHER FILMS as low as \$2.19 100 ft.
All prices include processing.
Send For Circular.

Fotoshop, Inc.

136½A West 32nd St., New York City

GOERZ

Announces . . .

a typical service rendered in our workshops—a service that may not be as familiar as it should be. We build to the exacting and particular specifications of advanced amateurs in Still and Cine Photography—apparatus requiring the highest type of technical precision in its construction.

What are your problems?

C. P. Goerz American Optical Co.
317 East 34th St. New York

Wheels of Industry

Continued from Page 540

35mm Sound Recording Camera is presented herewith, showing the operating side of this new DeVry product. Beginning at the top, note the adjustable belt idler at the rear of the magazine for positive take-up tension. Film footage counter at the rear of the camera. The focusing lens eye piece is just at the left and a little below the footage counter. Recording lamp socket is at the right of the eye piece. The Tachometer dial slit may be seen just above the motor governor knob. The Precision focusing and view finding is a notable feature.

Microscopic Movies

● Through the cooperation of the Bausch & Lomb Optical Co. and the Eastman Kodak Company, a new apparatus has been designed for making microscopic movies. The use of the 16mm camera has previously been somewhat limited in the scientific field. The cost of fitting up a movie camera to make microscopic movies ran well over the thousand dollar mark and was limited more or less to 35mm cameras and film.


Now the Cine-Kodak Special may be used with a special observation eyepiece, developed by Bausch & Lomb, which acts as a beam splitter. The beam splitter eyepiece is fitted to the front of the camera in place of the regular camera lens. In the beam splitter is a 45 degree prism, silvered but unbacked, which causes part of the light to be reflected to the film and part to be transmitted through the eyepiece so that the operator can observe the action and the field while the picture is being made.

The Observation Eyepiece sets into a flange placed on the microscope eyepiece so that a light tight seal is made between the two elements. This accessory can be fitted to any microscope.

Not only can films be easily made in black and white, but with the new Kodachrome film pictures in natural color can be obtained. The use of color film with polarized light produces some extraordinary results. The growth of crystals of organic compounds in regular and slow motion, filmed with polarized light, gives a mixture and change of color in the crystals of extraordinary beauty.

"Senior Solarspot"

● Since its introduction several months ago, Mole-Richardson's 2,000-Watt "Junior Solarspot" has made noteworthy strides in displacing the 18-inch reflecting spotlight as the Industry's standard lighting unit. This month Mole-Richardson has announced a larger companion-unit of the same type, the 5 KW "Senior Solarspot," designed to take in the new line the place occupied in older



Now Available NEW CINE NIZO 8mm Movie Camera

incorporating the very Latest Features found previously only in 16mm Equipment:

Standard outfit; well known Steinheil F:2.8—12.5mm Lens. Variable speeds 8, 16, 32, 64 Frames per second with intermediate speeds.

Three-in-One—Eye Level—Waist Level—and Right Angle—Finder!

Price \$65.00

Extra Equipment: High Speed Leitz F:1.5—12.5mm Lens. Telephoto Lenses F:2.8—35mm and 50mm, furnished with Filter.

Camera uses Eastman 8mm Film.

Cine Nizo Movie Camera has been awarded Gold Medals and taken many First Prizes in International Movie Contests!


Trade discounts to Dealers.

HANS UNFRIED

20 CAMP ST.

BUFFALO, N.Y.

Cinematographic Annual, Vol. 1 - Now \$2.00



16 MM. SOUND RECORDER

Berndt-Maurer presents a complete 16mm. double system Sound-On-Film Recorder designed for high quality results, convenient operation and complete versatility. Priced at \$630. as shown.

Write for illustrated description.

THE BERNDT-MAURER CORP.
117 EAST 24TH STREET • NEW YORK



BROOKS PRODUCTS for MOVIE MAKERS

- **SCHNEIDER XENON f/1.5**—Superspeed lens for 16mm. cameras, almost 12 times faster than f/4.5. Unsurpassed for poor light. Highly corrected, \$70.00. Other Schneider lenses from 1" to 4" focus.
- **TRIPODS**—Pocket, Linhof, Riess. Triax; Tripod Circular on application.
- **RAMSTEIN-OPTOCHROME**—Optical Glass Filters. Non-gelatine. All colors. \$3.00 up.
- **BADGLEY FILTER HOLDER**—Fits all lenses 1½" and smaller, \$2.85.
- **AUTOMATIC DISSOLVE**—For "fadein," "fadeout" and double exposure work. Professional results obtained with ease by any amateur. \$22.50.
- **FOCUSING PRISM**—Ground Glass. A precise method for focusing cine lenses in place on the camera. \$4.50.
- **BEE BEE DISTANCE METER**—for Cine or Still cameras. Enables you to obtain sharp focus, at a glance, within any distance from 2 ft. to infinity. \$4.20.
- **PHOTO FLOOD-SPOT**—New. Efficient, Versatile. For Professional spotlighting effects, such as fire-place shots, sun-kissed hair, etc. Has focusing rod for regulating intensity and area of light. Precision make. \$16.50.
- **NORTHEAST REFLECTORS**—Provide brilliant, super-actinic illumination. 75c up.
- **CAMERAS and ENLARGERS**—Rolleiflex, Rolleicord, Certo, Bee Bee, Linhof, Derby, Kawee and many other types.

Literature on Request.

BURLEIGH BROOKS

127 West 42nd Street

New York

Announcing

The Installation of Developing Machines

for Both 35mm and 16mm
and a New PB14181

**R C A PHOTOPHONE
OPTICAL REDUCTION
S O U N D P R I N T E R**

the foremost film laboratory of the
Middle West Continues to Lead!

—o—

Largest, most modern, most
completely equipped motion
picture laboratory between
New York and Hollywood.

Complete Motion Picture Service
RCA "High Fidelity" Recording

Write for Prices

Burton Holmes Films, Inc.

7510-14 N. Ashland Ave.

Chicago, Ill., U.S.A.

series by the 5 KW 24-inch reflecting Sunspot.

The beam of the "Senior Solarspot" may be concentrated to a spot-beam of 10 degrees or less, and flooded out to a spread of over 44 degrees. At the widest spread, the beam is said to retain sufficient intensity to be of photographic value.

The new lamp is a more compact unit than other types of the same wattage. It is built for convenient operation, with the tilt-locking handle carried through the housing to the rear, and all other operating controls conveniently grouped.

Victor Wipe-off

● Broadening the scope of his Du-Morr Radial Wipe for use beyond the Cine Kodak special, J. D. Cochrane, Jr., announces this device now available for the

Victor Model No. 5. This device produces 12 types of wipes with each shape of fan. It weighs only one pound and is said to be easy to operate.

DaLite Unipod

● The Dalite Screen Company of Chicago announces the No. 2 Unipod for holding substandard cameras. This accessory is made of two aluminum tubular members which telescope. The tip of the inner tube is provided with a threaded element to receive the camera; this is protected by an adjustable bakelite knob. By giving the knob a half turn, the Unipod is instantly extended to any length desired up to 17½ inches. It is supported by means of a strap around the neck. When the Unipod is collapsed, it is eleven inches long. It weighs 10 ounces.

Continuity for a Christmas Comedy

Continued from Page 534

Scene 30. CLOSE-UP of Buddy, with his face close to window-glass.

Scene 31. LONG-SHOT through store-window, showing Christmas display of toys.

Scene 32. Medium LONG-SHOT of entrance to a big department-store. Buddy and father go in.

Scene 33. Montage of SHOTS inside toy-department, CLOSE-UPS of various toys—especially electric trains.

Scene 34. Medium LONG-SHOT of Santa Claus, sitting down. A little girl is on his lap. She leaves, and Buddy comes up.

Scene 35. CLOSE-UP of Buddy, talking earnestly.

TITLE: "— an' I want some skates, a sled an' an electric train—"

Scene 36. CLOSE-UP of Santa, nodding approval. FADE OUT.

Scene 37. FADE IN. CLOSE-UP of calendar (stop motion). The leaves melt away until DECEMBER 25 is reached. FADE OUT.

Scene 38. FADE IN. LONG-SHOT in living-room, toward door. The door opens, and Father, Mother and Buddy enter.

Scene 39. CLOSE-UP of Christmas-tree, with presents grouped around it. Very prominent in foreground is a big package that looks as though it might contain a train.

Scene 40. Same as Scene 38. All advance toward camera—Buddy running forward.

Scene 41. CLOSE-UPS *ad lib* of the family opening their presents. Father is seen to get a fine new pipe and some neck-ties, and Buddy opens the big package, revealing a fine electric train.

Scene 42. CLOSE SHOT of Buddy, seated on floor, starting to set up his train and tracks.

Scene 43. MEDIUM-SHOT of same. Father drops down beside Buddy, and starts to help him. They commence to argue: Father apparently wants the tracks one way, and Buddy another. LAP-DISSOLVE (or fade out and in) TO

Scene 44. CLOSE-UP of electric train running around the track, which is arranged the way Father wanted it.

Scene 45. MEDIUM-SHOT of same. Father is playing with the train, having a lot of fun: Buddy is nowhere to be seen.

Scene 46. LONG-SHOT of same. Part of Christmas-tree in foreground, Father and the train in middle distance. Away off in the background, Buddy is seated in a chair.

Scene 47. CLOSE-UP of Buddy in the chair. He has Father's pipe, at which he is looking very disgustedly. Finally he puts the pipe down, and gets up resolutely.

Scene 48. MEDIUM-SHOT. Buddy ap-

DO YOUR FILMS CONSTITUTE AN IMPERISHABLE RECORD!

TEITEL'S SCRATCH PROOF SOLUTION
Protects your film against scratching, abrasions, gumming, buckling, time, use and the elements.

TEITEL'S NEW LIFE SOLUTION
Revives your film, generally prolongs its life and prevents deterioration of new film.

Both solutions are intended for the use of the amateur who is able to treat his own films—at home—whenever the necessity arises.

Price per 6-oz. bottle. \$1.00

Booklet "Y" on request

KIN-O-LUX 105 West 40th Street
New York

proaches a writing-desk, sits down, draws out a piece of paper, and starts to write.

Scene 49. Insert of letter Buddy is writing. It reads:

Dere Santy:

I got the lectrick trane all write.
But sAy, Santy, you gotta be more careful. Daddy thinks its hiS.
Cantchu do sompn about it sAnty?
If you dont I aint gonna be good no more.

Buddy.

Scene 50. CLOSE-UP of Buddy. He looks off to one side.

Scene 51. LONG-SHOT, past Buddy, to where Father is playing with train.

Scene 52. MEDIUM-SHOT of Buddy. He turns back, and resolutely signs the note.

Scene 53. CLOSE-UP of the train coming straight into the camera.

THE END.

Additional parts can be written into this, of course, for neighbor children, or other members of the family. The street-car scenes are best made on a

Sunday, when there is less traffic. The shot of Buddy in the car can be eliminated if it doesn't seem practical, though in most street-cars it can be made easily on a sunny day. It would be advisable, incidentally, to use the shaded side of the street for a background in this shot, to equalize the exposure. The shots of Buddy, and of Buddy and Father on the downtown streets can be 'stolen' by putting the camera inside a car and shooting through the window. The close-ups of the children looking into the store-window can be made at any time, using any old window-pane for the glass, and shooting so as to miss the frame.

If, as is probable, you can't find enough light in a toy-department to make the Montage (Scene 33) in motion pictures, make it up by copying, (in a title-board) still shots made with a Leica, or photos from toy catalogues, etc. The scenes of Santa Claus can be made at home, with Father doubling for Santa, and a plain white sheet serving as the background, for Santa often uses a tent in toy stores.

Filming Snow Scenes With Filters

Continued from Page 532

beautiful "normal" or "natural" effects. The secret of securing correct tonal quality in snow is, then, in the use of a panchromatic film and a filter.

Another considerable aid in good snow results is an exposure meter. In the winter-time, the light is not nearly so intense as in summer, although the brilliant reflection in the snow may lead one to believe that the light is more intense than it really is. Of course the snow reflects sunlight to a surprising degree and must therefore be taken into consideration, but just how much to allow is something best left to a reliable exposure meter. The photronic cell type of meter is especially recommended, for its infallible readings can be depended upon at all times, whereas the extinction type of meter is apt to lead one astray because of the intensity of the reflected light affecting the eyes when making a reading. Exposure in snow filming is something not to be lightly tossed aside, for it is a vital and influential matter. Probably more footage is wasted yearly because of the lack of reliable exposure than any other single cause. Use a meter, then, for best results.

Thus far we have considered only the filming of snow scenes in sunlight. How about when it snows? Isn't there a possibility here? Most assuredly there is, for the downy flakes falling idly make amazing cinematic patterns on the screen which are well worth recording. Naturally a filter is out of the question in such cases because there is not suf-

ficient illumination, as a rule, to stand it, and secondly there is no purpose in using one. Leave the filter off the lens; use a fast film and a speedy lens—you will be surprised as to what you get.

One delightful feature of snow photography, which has rarely been mentioned, is the photography of what is commonly called hoar-frost. It occurs only rarely, and then lasts only a short while, hence demands the greatest observance and preparedness of the filmer. In early spring, when a rain falls instead of snow, the weather may suddenly freeze, causing the rain-water to freeze, thus coating whatever it covers with a gorgeous, silvery layer which sparkles and shines in the sun's rays. Trees, bare and stark, in the park or in the country, are particularly picturesque, their branches enveloped in an icing which resembles cellophane. If such subjects can be caught in the proper light, fascinating scenes can be captured before they disappear. Icicles, too, when hanging from roof-tops, offer interesting pictorial patterns, and should not be ignored, for a few such odd shots might later fit in splendidly with some other subject-matter.

Of course winter sports should not be ignored. Skating, skiing, tobogganing, and similar activities offer a wealth of material for the serious filmer. It is sometimes difficult to tie such action shots in with picturesque backgrounds, but the enthusiast can usually manage to combine the two into a most effective



Ampro

Bass offers the biggest bargain in the industry. This 16mm AMPRO is equipped with 400-watt Biplane Mazda equal illumination to 500 watt. High power cooling system, high speed mechanical re-wind. Centralized controls. Silent fibre gears. Forward and reverse. Over-size motor. Ideal for Kodachrome. Light weight. Ampro exclusive tilt. Originally \$135. At Bass only \$99.50.

ORDER DIRECT

from this ad. BASS personally guarantees 100% satisfaction. Your money back without red tape. BASS takes your present equipment as part payment. Write to BASS for details: BASS Bargaingram and catalog of other Ampro Models. Get the new BASS large catalog of 16mm silent and Sound-on-Film Library.

... **BASS** ...
CAMERA COMPANY
179 W. Madison St., Chicago

DEPT. D

reel. Angle shots are particularly powerful, especially when shooting skaters and skiers. Low angles as a rule are most forceful and should be secured whenever possible, for they are not as common as one might suppose.

Even if no special use can be thought of for such scenes, they should be secured, for when they are needed, they are awfully difficult to get. Therefore, don't lose any opportunities to get snow and ice scenes. If they are pictorial, all the better. Snow subjects are exceedingly rare, and because no dependence can be placed upon the weather, it behooves every filmer interested in snow scenes to get them whenever possible.

Definitions of Elements in Composition

Continued from Page 536

in a mad whirl. The head falls from the body into the waste-paper basket, where most authors' brain-children find peace and rest. By cutting in close-up shots of showing only two eyes looking in the direction of the related action we never let the audience know if they are seeing a living person or if it is really a dummy. In the last fade-out we see the head with all the straw and sawdust strewn about, when suddenly the eyes close in death as a shower of other unwritten plots comes tumbling down upon the headless author until they have quite obliterated our hero, (if we ever had one.) By pasting scare-heads from local newspapers so that they spell the end, you can give a good finish to this nightmare plot.

CAST: Dummy Figure
Hands

Typewriter
Waste-paper Basket

CLOSE-UP: Hands typing out Main Title.

CLOSE-UP: Hands furiously hitting keys.

CLOSE-UP Under-shot of hands in action of typing.
(Use glass to shoot through from under side.)

DISSOLVE into CLOSE-UP of dummy's eyes.

DISSOLVE into CLOSE-UP of dummy's head.
(Cut out masking frame for shooting all shots in dummy's brain.)

CLOSE-UP (FADE IN) First action scene of wheels moving.

DISSOLVE to wheels going in opposite direction.

DISSOLVE into hands hammering with downward motion.

(Increase tempo of this action.)

CLOSE-UP: Eyes looking into direction of action.

CLASSIFIED ADVERTISING

Rates: Seven cents a word. Minimum charge, one dollar per insertion.

FOR SALE—MISCELLANEOUS

35mm NEGATIVE fresh Eastman and Dupont stock — panchromatic — supersensitive — grayback, \$2.50 per hundred feet. 100 ft., daylight loading rolls, \$2.75 each. Leica rolls 36 exposures. 10% discount on all orders accompanied by this coupon.
PACIFIC COAST RAW FILM CO., 1558 No. Vine St., Hollywood, California. T

SEVERAL Holmes Projectors 35mm, excellent condition. Full Guarantee. Prices \$75.00 to \$95.00. Camera Supply Co. Ltd. 1515 Cahuenga Blvd., Hollywood, Calif.

VERY powerful Floodlights of new design. Will burn through a 1000 W Rifle. Reflector with Gable \$5.00. With 12-foot collapsible stand \$22.50. Camera Supply Co. Ltd., 1515 Cahuenga Blvd., Hollywood, Calif.

POWERS CINEPHONE RECORDERS WITH SLIT BLOCK AND SYNCHRONOUS MOTOR \$200.00 each. J. Burgi Contner, 723 Seventh Ave., New York City. T

WE BUY, SELL AND RENT PROFESSIONAL AND 16mm EQUIPMENT NEW AND USED. WE ARE DISTRIBUTORS FOR ALL LEADING MANUFACTURERS. RUBY CAMERA EXCHANGE, 729 Seventh Ave., N. Y. C. Established since 1910.

DIRECT POSITIVES. You make them. Make them for others. Complete detailed instructions, 25c. MACART, box 1947, Hollywood, Calif.

35mm DeVRY CAMERA \$50.00. Eyemo f 2.5 camera with case \$85.00. DeVry Super portable projector \$45.00. Many 16mm bargains, also library, catalogue. MOGULL'S, 1944-A Boston Road, New York.

TWO DUPLEX 35mm. Printers, one equipped with Bell-Howell Camera Shuttles Dead Accurate Registration. Can be used for color or black and white. One is a skip printer. Priced low for quick sale. Cinema Arts & Crafts, 918 No. Fairfax, Hollywood, Calif.

230-DEGREE Shutter Akeley Camera X134, special focus on film attachment. 2-, 4-, 6-, and 12-inch lenses. Four 200-foot magazines, Akeley tripod, cases. Price \$750.00. Motion Picture Camera Supply, Inc., 723 Seventh Ave., New York City; Cable: Cinecamera. T

FOR SALE: Silent Mitchell Camera. Complete price \$2,500.00. Box 254, care American Cinematographer.

EYEMO, SOUND SPEED, filter-holding shade. Best offer; trade Victor Five, Eastman Special. 17011 Elsienna, Cleveland.

DISSOLVE into quick shots of people's feet, hands, and any moving object.

(Every three or four shots cut back to EYES.)

Note: Build up tempo with quick shot of the harassed brain, until the structural forms melt into one continuous action. In this shot it would be good to let smoke cover the frame and suddenly break into flames.

CUT BACK to eyes. They should have a terror-stricken look.

DE BRIE HIGH SPEED CAMERA: two 400-ft. magazines, De Brie heavy duty tripod, 2" lens. Motion Picture Camera Supply, Inc., 723 Seventh Avenue, New York City; Cable: Cinecamera. T

2 Akeley Cameras, Modern Studio equipment. Late models. Full range of lenses. Prices \$850.00 and \$950.00. Camera Supply, Ltd., 1515 Cahuenga Blvd., Hollywood, California.

SILENCED Bell & Howell with check pawl shuttle 40, 50, and 75mm F. 2.7 lenses mounted, 2 1000-ft. Magazines, tripod, finder and sunshade. Rebuilt like new. Motion Picture Camera Supply, Inc., 723 Seventh Avenue, New York City; Cable: CINECAMERA. T

ARTREEVES latest 1935 portable double sound recording unit with double sprocket recorder, automatic speed control motor, twin fidelity optical unit. Latest type camera motor. New type microphone. Complete factory guaranteed, \$2,400. This is the only authentic ArtReeves equipment for sale in Hollywood outside factory. Slightly used ArtReeves sound equipment complete \$1,800.00. Camera Supply Co., Ltd., 1515 Cahuenga Blvd., Hollywood, Calif.

3 Bell & Howell five-way Sound Printers, Motor generators, panel control boards. Duplex Printer, especially adapted for duping Sound and silent Movielas; Educational Blimp and Dolly; Bell & Howell splicers. Title Board with lathe bed; Bell & Howell silent cameras, Bell & Howell motors, Bell & Howell high-speed gear box, Mitchell and Bell & Howell Friction head tripods. Above equipment used but in perfect mechanical and optical condition at bargain prices. Hollywood Camera Exchange, Ltd., 1600 No. Cahuenga Blvd., Hollywood, California. Cable address: HOCAMEX.

SILENCED Bell & Howell with new Fearless Movement 40, 50, and 75mm F. 2.7 lenses mounted. 2 1000-ft. Magazines, tripod, finder and sunshade. Perfect condition. Motion Picture Camera Supply, Inc., 723 Seventh Avenue, New York City; Cable: CINECAMERA. T

WANTED

WANTED—Mitchell or Bell & Howell 35mm Camera. Box 253 American Cinematographer.

WILL PAY CASH FOR: Bell & Howell, Mitchell, Akeley or De Brie Cameras, lenses, motors, parts and accessories. Motion Picture Camera Supply, Inc., 723 7th Ave., New York, New York. T

WANTED. Eyemo or DeVry camera, good condition, reasonable. E. Traung, 861 Manhattan Ave., Brooklyn, N. Y.

WANTED. We pay cash for everything photographic. Send full information and lowest cash prices. Hollywood Camera Exchange, 1600 Cahuenga Blvd., Hollywood, Calif.

CLOSE-UP of head in full frame; hold shot as head starts rocking until it falls from body.

CLOSE-UP of waste-paper basket, head falls into basket.

CLOSE-UP of eyes closing, basket is littered with saw-dust, manuscript paper falls over head and eyes, hiding completely the scene.

FADE OUT and bring in TITLE;

"THE END."

WINNERS *of* Amateur Movie Contest

Will be announced in the next issue,
bearing date of January, 1935

•

Be sure to reserve your copy right now from your dealer
if you are not a regular subscriber. We will not be able
to furnish this issue after the month is over if the de-
mands are as big as in previous years.

•

JANUARY ISSUE

is the Contest Winner Issue

*Reserve Your Copy Right Now from
Your Dealer*

Season's Greetings

to
Cinematographers
the World Over



Mitchell Camera Corporation

665 N. ROBERTSON BOULEVARD
WEST HOLLYWOOD, CALIF.

Cable Address "MITCAMCO"

AGENCIES

Phone OXford 1051

CLAUD C. CARTER
Sydney, Australia

MOTION PICTURES CAMERA SUPPLY INC., New York City

D. NAGASE & CO., Ltd.
Osaka, Japan

BOMBAY RADIO CO.,
Ltd.
Bombay, India

ARMINIO CONTI,
Rome, Italy

H. NASSIBIAN
Cairo, Egypt